

Title (en)
LEAK DETECTION APPARATUS.

Title (de)
LECKERKENNUNGSGERÄT.

Title (fr)
APPAREIL DE DETECTION DE FUITES.

Publication
EP 0046748 A4 19820903 (EN)

Application
EP 80900528 A 19800222

Priority
US 8000180 W 19800222

Abstract (en)
[origin: WO8102484A1] A leak detection apparatus (18) is provided in a pressurized assembly (10) to signal a loss of pressure or vacuum downstream from a source of pressure or vacuum. A rod (60, 160, 260) is carried on a valve (62, 162) and a diaphragm (38, 138) which seals the source of pressure or vacuum from the system. A loss of pressure or vacuum downstream of the valve (62, 162) and diaphragm (38, 138) moves the rod (60, 160, 260) to a signalling position to alert an interested party that the system is lacking pressure or vacuum.

IPC 1-7
G08B 21/00; **F16K 37/00**; **H01H 35/24**

IPC 8 full level
A62C 37/50 (2006.01); **F16K 37/00** (2006.01); **F17D 5/02** (2006.01); **G01L 19/12** (2006.01); **G01M 3/26** (2006.01); **G01P 5/00** (2006.01); **G08B 21/00** (2006.01)

CPC (source: EP)
A62C 37/50 (2013.01); **F16K 37/00** (2013.01); **G01L 19/12** (2013.01); **G01M 3/26** (2013.01)

Cited by
CN112833270A

Designated contracting state (EPC)
FR GB

DOCDB simple family (publication)
WO 8102484 A1 19810903; CA 1152605 A 19830823; EP 0046748 A1 19820310; EP 0046748 A4 19820903; JP S57500125 A 19820121

DOCDB simple family (application)
US 8000180 W 19800222; CA 360966 A 19800924; EP 80900528 A 19800222; JP 50068580 A 19800222