

Title (en)

Writing liquid storage control device for ink jet writing systems.

Title (de)

Vorrichtung zur Überwachung des Vorrates an Schreibflüssigkeit in Tintenschreibeinrichtungen.

Title (fr)

Dispositif de surveillance de stockage de liquide à écrire dans un système de jet d'encre pour machine à écrire.

Publication

EP 0047478 A2 19820317 (DE)

Application

EP 81106841 A 19810901

Priority

DE 3034067 A 19800910

Abstract (en)

[origin: US4380019A] A mechanical device for monitoring the supply of ink in an ink storage reservoir carried by the printing carriage of an ink printing device is situated at one end of the path of movement for the printing carriage. The ink reservoir is mounted on the printing carriage and contains a freely reciprocable tappet member having an upstanding stem extending through the housing cover of the ink reservoir which is freely movable up and down in accordance with the level of remaining ink supply. The mechanical monitoring device is operated dependent upon the vertical position of the tappet stem each time a printing operation is begun by virtue of movement of the printing carriage toward the monitoring device so that the relative position of the tappet member may be sensed by the device. The mechanical monitoring device comprises a pivotable lever arm disposed perpendicular with respect to the movement path of the ink reservoir and printing carriage to be laterally engaged by the tappet in the event that the ink supply is sufficient and the tappet is upraised. When the lever arm is engaged, its lateral movement triggers an electrical switch which operates an electrical circuit to indicate to the operator that the ink supply is adequate. When the ink supply is too low, the tappet is lowered such that the tappet passes beneath the lever arm without engaging and the switch is not triggered, causing an alarm signal to be actuated on the ink printing device informing the operator to replenish the ink supply.

Abstract (de)

Vorrichtung zur Überwachung des Vorrates an Schreibflüssigkeit in Tintenschreibeinrichtungen. Am seitlichen Rand eines die Tintenvorratsflasche (3) tragenden Schreibwagens (2) befindet sich eine mechanische Fühleinrichtung für den Tintenvorrat. Sie besteht aus einer entgegen einer Federkraft schwenkbaren gabelförmigen Schaltschwinge (8) mit daran ausgebildetem Gleitstück (9) und einer Auflaufschräge (10) für den Gehäusedeckel (6). Senkrecht zu diesem Gleitstück ist ein entgegen einer Federkraft schwenkbar angeordneter Tasthebel (12) angeordnet, der einen aus dem Gehäusedeckel ragenden, entsprechend dem Verbrauch an Tintenvorrat in den Gehäusedeckel eintauchenden Stösse (5) über einen elektrischen Schalter (13) abtastet.

IPC 1-7

B41J 3/04

IPC 8 full level

B41J 2/175 (2006.01)

CPC (source: EP US)

B41J 2/17566 (2013.01 - EP US)

Cited by

EP0308796A1; FR2779092A1; US6352325B1

Designated contracting state (EPC)

CH FR GB IT NL SE

DOCDB simple family (publication)

EP 0047478 A2 19820317; EP 0047478 A3 19830119; EP 0047478 B1 19841205; DE 3034067 A1 19820415; DE 3034067 C2 19870319; JP S5777579 A 19820514; JP S6344065 B2 19880902; US 4380019 A 19830412

DOCDB simple family (application)

EP 81106841 A 19810901; DE 3034067 A 19800910; JP 14042381 A 19810908; US 29736881 A 19810828