

Title (en)

A fuse link and the combination thereof in an expulsion fuse.

Title (de)

Schmelzleiter und dessen Kombination in einer Ausblasesicherung.

Title (fr)

Conducteur fusible et la combinaison de celui-ci dans un coupe-circuit à expulsion.

Publication

**EP 0047592 A2 19820317 (EN)**

Application

**EP 81303728 A 19810814**

Priority

US 18271980 A 19800829

Abstract (en)

A fuse link including a fuse element of known cross-sectional area having a number of holes centrally located therein to define reduced cross-sectional areas and a filler material provided in said holes, said embodiment having a short time-current melt characteristic at high overload substantially the same as the homogeneous fuse element and a long time-current melt characteristic different from the long time-current melt characteristic of the fuse element.

IPC 1-7

**H01H 85/04**; **H01H 85/40**

IPC 8 full level

**H01H 85/165** (2006.01); **H01H 37/76** (2006.01); **H01H 85/055** (2006.01); **H01H 85/06** (2006.01); **H01H 85/08** (2006.01); **H01H 85/10** (2006.01); **H01H 85/11** (2006.01); **H01H 85/40** (2006.01)

CPC (source: EP)

**H01H 85/055** (2013.01); **H01H 85/40** (2013.01)

Cited by

FR2583917A1; FR2583918A1; EP2874174A1; CN104934273A; US10553386B2

Designated contracting state (EPC)

AT BE CH DE FR GB IT LI NL SE

DOCDB simple family (publication)

**EP 0047592 A2 19820317**; **EP 0047592 A3 19820331**; BR 8105320 A 19820504; JP S5774933 A 19820511

DOCDB simple family (application)

**EP 81303728 A 19810814**; BR 8105320 A 19810820; JP 13537581 A 19810828