

Title (en)  
ELECTRO ACOUSTIC PLANAR TRANSDUCER

Publication  
**EP 0048434 B1 19850703 (EN)**

Application  
**EP 81107275 A 19810915**

Priority  
US 18875780 A 19800919

Abstract (en)  
[origin: US4385210A] An electro-acoustic transducer using thin, lightweight, planar diaphragms driven by strategically located, coil-driven, high-energy, permanent magnets. A framework maintains the diaphragms in substantially co-planar relationship a predetermined distance from and parallel to a rear support wall. The diaphragms include at least one hinged woofer diaphragm and a foam-supported tweeter diaphragm. The small, high energy movable permanent magnets are attached to the rear surface of each movable diaphragm. Cooperating with each movable magnet is a respective, stationary electromagnetic coil with a crossover network directing the incoming signal to the appropriate coils, thereby placing the magnets and attached diaphragms into cooperating fore and aft motion. The frontal acoustical waves produced by each woofer constructively interfere to augment low frequency response. The tweeter construction provides wide frontal dispersion of high frequency acoustical waves. Woofer backwaves are attenuated before emerging along the rear support wall and the tweeter backwave is vented into a rear isolative chamber.

IPC 1-7  
**H04R 11/02**; H04R 5/02; H04R 1/24

IPC 8 full level  
**H04R 1/24** (2006.01); **H04R 11/02** (2006.01)

CPC (source: EP US)  
**H04R 1/24** (2013.01 - EP US); **H04R 11/02** (2013.01 - EP US)

Cited by  
US4939784A; US7218749B1; WO0018180A1

Designated contracting state (EPC)  
DE FR GB IT SE

DOCDB simple family (publication)  
**EP 0048434 A1 19820331**; **EP 0048434 B1 19850703**; CA 1180437 A 19850102; DE 3171229 D1 19850808; US 4385210 A 19830524

DOCDB simple family (application)  
**EP 81107275 A 19810915**; CA 386221 A 19810918; DE 3171229 T 19810915; US 18875780 A 19800919