

Title (en)
ZINC OXIDE VARISTOR AND METHOD FOR PROVIDING SUCH VARISTOR

Publication
EP 0050735 B1 19870311 (EN)

Application
EP 81107413 A 19810918

Priority
US 20118280 A 19801027

Abstract (en)
[origin: US4317101A] A high voltage varistor for DC operation is manufactured by applying a glass collar to the perimeter of a sintered zinc oxide disc and heat treated between about 750 DEG C. and 400 DEG C. for several cycles in air. After heat treating, an organic resin or ceramic coating is applied to the glass collar to further insulate the varistor for high voltage application.

IPC 1-7
H01C 7/10; **H01C 17/00**

IPC 8 full level
H01C 7/10 (2006.01); **H01C 7/102** (2006.01)

CPC (source: EP US)
H01C 7/102 (2013.01 - EP US); **Y10T 29/49101** (2015.01 - EP US)

Cited by
DE3405834A1

Designated contracting state (EPC)
CH DE LI SE

DOCDB simple family (publication)
US 4317101 A 19820223; BR 8106613 A 19820629; CA 1186760 A 19850507; DE 3175989 D1 19870416; EP 0050735 A1 19820505; EP 0050735 B1 19870311; JP H0136241 B2 19890731; JP S57100703 A 19820623; MX 150912 A 19840815

DOCDB simple family (application)
US 20118280 A 19801027; BR 8106613 A 19811009; CA 388033 A 19811015; DE 3175989 T 19810918; EP 81107413 A 19810918; JP 17089081 A 19811027; MX 18984381 A 19811027