

Title (en)

STOPPER FOR BOTTLES FOR THE STERILE PRESERVATION AND POURING OUT OF LIQUIDS

Publication

EP 0052175 B1 19840912 (DE)

Application

EP 81101601 A 19810306

Priority

- DE 3043130 A 19801115
- DE 8030566 U 19801115

Abstract (en)

[origin: EP0052175A1] 1. Bottle seal made from an elastic material to keep and allow liquids to be poured out in a steril condition, consisting of an annular neck section (2), the free end of which can be inserted into the cylindrical hole (1A) of the bottle aperture (1), a single-piece annular disc-shaped rim section (3) which is moulded onto the outer end of the neck section (2), projects radially beyond this and extends into the outer top end (1B) of the bottle aperture (1), and a single-piece almost disc-shaped bottom part (4) which is moulded onto the neck section (2) and fills the central area surrounding that section. This bottom part (4) is on or near the inner end of the neck section (2) facing the inside of the bottle, and is provided with a gripper nose (6) in the cup-shaped hollow (5) formed by the internal circumference (2A) of the neck section (2) and the outer area (4A) of the bottom section (4). The characteristic feature of this seal is that the gripper nose (6) is moulded in a single-piece to the inner circumference (2A), extend to the bottom section (4) and is connected therewith, and also has a plane of symmetry (S) with the central axis (M) of the seal, having lateral boundary surfaces (6A, 6B) lying essentially parallel or at an angle of 10 degrees maximum to the plane of symmetry (S), with its radial inner boundary surface (6C) positioned at a distance from the diametrically opposite side of the inner circumference (2A), and that the gripper nose (6) is divided into an inner nose section (6') and an outer nose section (6'') by a cut or slit (6) beginning at the radial inner boundary surface (6C) and extending in the direction of one side of the inner circumference (2A).

IPC 1-7

B65D 39/16

IPC 8 full level

B65D 39/16 (2006.01); **B65D 51/00** (2006.01)

CPC (source: EP)

B65D 39/16 (2013.01); **B65D 51/002** (2013.01)

Designated contracting state (EPC)

AT BE CH FR GB IT LI LU NL SE

DOCDB simple family (publication)

EP 0052175 A1 19820526; **EP 0052175 B1 19840912**; DE 3043130 A1 19820701; DE 8030566 U1 19810521

DOCDB simple family (application)

EP 81101601 A 19810306; DE 3043130 A 19801115; DE 8030566 U 19801115