

Title (en)

PRINTING MECHANISM WITH A RECORDING ELEMENT AND MEANS FOR THE ROTATION OF A RECORD CARRIER

Publication

EP 0052408 A3 19830907 (DE)

Application

EP 81201267 A 19811116

Priority

DE 3043630 A 19801119

Abstract (en)

[origin: US4437780A] For the reliable guiding of a record carrier and the printing thereon as far as in the vicinity of the upper and lower edge, a pivotable device is arranged over the printing drum, said device comprising two or more flat hold-down devices which are arranged on a rotatable shaft. The hold-down devices can be slid into a first position in which they engage the printing drum and a second position in which they are lifted off the printing drum. In the first position, the record carrier is deflected to the printing drum during transport, and in the second position it is transported by additional pressure rollers. The device is pivotable about the printing drum into three positions and is constructed as a modular unit. This enables the simultaneous or alternating transport about the printing drum of different record carriers in a different manner.

IPC 1-7

B41J 13/10

IPC 8 full level

B41J 13/00 (2006.01); **B41J 13/02** (2006.01); **B41J 13/10** (2006.01); **B41J 15/04** (2006.01); **B41J 19/20** (2006.01)

CPC (source: EP US)

B41J 13/10 (2013.01 - EP US)

Citation (search report)

- [A] DE 1238934 B 19670420 - IBM
- [A] DE 666330 C 19381017 - ERWIN O HABERFELD

Cited by

GB2168291A; DE9000255U1; GB2203700A; GB2203700B; EP0118318A3; EP0649749A1; US5447384A

Designated contracting state (EPC)

DE FR GB IT

DOCDB simple family (publication)

EP 0052408 A2 19820526; EP 0052408 A3 19830907; EP 0052408 B1 19850605; DE 3043630 A1 19820708; DE 3170889 D1 19850711; JP H0229510 B2 19900629; JP S57113089 A 19820714; US 4437780 A 19840320

DOCDB simple family (application)

EP 81201267 A 19811116; DE 3043630 A 19801119; DE 3170889 T 19811116; JP 18241881 A 19811116; US 32077881 A 19811112