

Title (en)

EXTRUSION METHOD

Publication

**EP 0053510 B1 19850522 (EN)**

Application

**EP 81305652 A 19811130**

Priority

JP 16991880 A 19801129

Abstract (en)

[origin: EP0053510A2] A method and apparatus for hot lubricated metal extrusion in which a billet is extruded into a solid or tubular form by means of a die and/or a mandrel with an organic lubricant interposed within a container, the method comprising feeding a combustion improver or a mixture of a combustion improver and water to the surface of the extruded product to burn off the carbide of the lubricant deposited on the surface of the extruded product.

IPC 1-7

**B21C 43/00; B21C 23/32**

IPC 8 full level

**B21C 23/08** (2006.01); **B21C 23/00** (2006.01); **B21C 23/32** (2006.01); **B21C 43/00** (2006.01)

CPC (source: EP)

**B21C 23/007** (2013.01); **B21C 23/32** (2013.01); **B21C 43/00** (2013.01)

Cited by

US6708752B2; WO03055626A1; WO02085560A1; US7427190B2; US7934627B2; US6712125B2; US6712126B2

Designated contracting state (EPC)

DE FR GB

DOCDB simple family (publication)

**EP 0053510 A2 19820609; EP 0053510 A3 19820714; EP 0053510 B1 19850522**; CA 1191480 A 19850806; DE 3170645 D1 19850627;  
JP S5791822 A 19820608; JP S6144563 B2 19861003

DOCDB simple family (application)

**EP 81305652 A 19811130**; CA 390886 A 19811125; DE 3170645 T 19811130; JP 16991880 A 19801129