

Title (en)  
PROCESS FOR THE MANUFACTURE OF DECORATIVE LAMINATES

Publication  
**EP 0054405 B1 19850213 (EN)**

Application  
**EP 81305807 A 19811209**

Priority  
GB 8039933 A 19801212

Abstract (en)  
[origin: EP0054405A1] A process for the manufacture of a decorative laminate utilises a decorative laminate surface or overlay paper carrying a coating comprising a pigment and a binder. This coating affords improved printability without unacceptably reducing absorbency towards impregnating resins. The Gurley porosity of the coated paper is about 10-70 sec/100 ml; and the coating is present at a dry coatweight of up to 10 gm<-><2>, preferably 2.5 to 3 gm<-><2>. The coating is preferably applied by means of a size press. Laminate manufacture using the paper is conventional.

IPC 1-7  
**D21H 5/00**; **B41M 1/36**; **B41M 7/00**; **B44C 5/04**

IPC 8 full level  
**B32B 27/10** (2006.01); **B32B 27/04** (2006.01); **B32B 27/20** (2006.01); **B44C 5/04** (2006.01); **D21H 19/12** (2006.01); **D21H 27/02** (2006.01); **D21H 27/26** (2006.01)

CPC (source: EP)  
**B44C 5/0469** (2013.01); **D21H 27/26** (2013.01)

Cited by  
WO2009097986A1; WO2005116337A1; EP0122589A3; EP1044822A1; GR1000651B; AU684426B2; FR2870265A1; EP3496945A4; EP2233287A1; US6706372B2; WO2010108568A1; WO9715430A1; WO9901296A1; US9567713B2; WO2004007215A1; WO9717214A1; US10124603B2; US10994555B2; US11613133B2; US11794460B2; US10214028B2; US10549550B2; US10807385B2; US10814648B1; US11446938B2; US11987044B2; US10471769B2; US10906349B2; US11465439B2; US11878548B2

Designated contracting state (EPC)  
DE FR GB IT

DOCDB simple family (publication)  
**EP 0054405 A1 19820623**; **EP 0054405 B1 19850213**; CA 1170513 A 19840710; DE 3168974 D1 19850328; JP S57501950 A 19821104; WO 8202067 A1 19820624

DOCDB simple family (application)  
**EP 81305807 A 19811209**; CA 392250 A 19811214; DE 3168974 T 19811209; GB 8100266 W 19811209; JP 50003082 A 19811209