

Title (en)

METHOD AND DEVICE FOR COOLING THE PRIMARY CIRCUIT OF A PRESSURIZED WATER REACTOR

Publication

EP 0055969 B1 19850327 (FR)

Application

EP 81402102 A 19811231

Priority

FR 8027859 A 19801231

Abstract (en)

[origin: US4486383A] A method of cooling the primary circuit of a pressurized water nuclear reactor in which, after a first stage, during which water is injected into the steam generators and the steam produced is discharged, cooling is continued during a second stage by water-water heat exchange. In this second stage, the water is made to circulate at the secondary side of at least one steam generator (2) in countercurrent to the primary water, over at least part of its path. The secondary water heated by the primary water is cooled outside the containment enclosure (1) of the nuclear reactor in at least one heat exchanger (31) using raw cooling water. The secondary water is recycled in the steam generator (2). The invention is applicable to the effecting an maintaining of cold shutdown of pressurized water nuclear reactors.

IPC 1-7

G21C 15/18

IPC 8 full level

G21C 15/18 (2006.01)

CPC (source: EP US)

G21C 15/18 (2013.01 - EP US); **Y02E 30/30** (2013.01 - EP US)

Cited by

GB2169743A; FR2594253A1; GB2161643A; US4666662A

Designated contracting state (EPC)

BE DE FR GB IT

DOCDB simple family (publication)

EP 0055969 A1 19820714; **EP 0055969 B1 19850327**; DE 3169629 D1 19850502; FR 2497387 A1 19820702; FR 2497387 B1 19850906; US 4486383 A 19841204

DOCDB simple family (application)

EP 81402102 A 19811231; DE 3169629 T 19811231; FR 8027859 A 19801231; US 32363681 A 19811120