

Title (en)

OBTURATOR AT THE EXTREMITIES OF A MACHINE FOR TREATING SHEET MATERIAL

Publication

EP 0056538 B1 19850306 (FR)

Application

EP 81401949 A 19811208

Priority

FR 8100288 A 19810109

Abstract (en)

[origin: US4463771A] The device provides an arrangement of the input and output ends of the machine which is of light and cheap construction, smaller in size and allows an adaptation of the machine in accordance with the width of the product to be treated. The device comprises, for each end of the machine, at least one rigid closing shutter carried by one of the frames of the machine. Guiding devices carried by this frame ensure a displacement of the or each shutter in a direction roughly perpendicular to the plane of the sheet passing through the machine. Devices for shifting the or each shutter are provided. The or each shutter cooperates by its free edge with the other frame of the machine so as to close in a substantially sealed manner the input or output end of the machine.

IPC 1-7

B21B 45/02; **C21D 9/54**

IPC 8 full level

B21B 45/02 (2006.01); **C21D 9/52** (2006.01); **C21D 9/56** (2006.01); **C21D 9/573** (2006.01)

CPC (source: EP US)

B21B 45/0218 (2013.01 - EP US); **C21D 9/573** (2013.01 - EP US)

Designated contracting state (EPC)

DE GB

DOCDB simple family (publication)

EP 0056538 A1 19820728; **EP 0056538 B1 19850306**; DE 3169209 D1 19850411; FR 2497829 A1 19820716; FR 2497829 B1 19860725; IT 1145217 B 19861105; IT 8168574 A0 19811203; JP S57164936 A 19821009; JP S6410577 B2 19890222; US 4463771 A 19840807

DOCDB simple family (application)

EP 81401949 A 19811208; DE 3169209 T 19811208; FR 8100288 A 19810109; IT 6857481 A 19811203; JP 166882 A 19820108; US 33851482 A 19820111