

Title (en)

USE OF RIGID FOAM PANELS FOR THERMAL INSULATION OF BUILDING FRONTS

Publication

EP 0056660 B1 19850807 (DE)

Application

EP 82100860 A 19800307

Priority

DE 7906824 U 19790312

Abstract (en)

[origin: EP0056660A2] 1. The use of 2 to 30 cm thick boards which consist of a rigid foam having a density of from 10 to 100 g/l, and are provided on at least one side with two sets of parallel incisions, and wherein the width of the incisions is from 0 to 1 mm and the depth thereof is greater than half the board thickness ; the distances between the incisions are from 3 to 30 cm ; and the two sets of incisions cross one another at an angle of from 75 to 90 degrees, for insulating the façades of buildings by fastening the boards to the façade and then applying a firmly adhering layer of finish to the outer face of the boards which is provided with incisions.

IPC 1-7

E04F 13/04; **E04C 2/20**

IPC 8 full level

E04C 2/20 (2006.01); **E04C 2/24** (2006.01); **E04C 2/284** (2006.01); **E04F 13/04** (2006.01)

CPC (source: EP)

E04C 2/205 (2013.01); **E04C 2/243** (2013.01); **E04C 2/284** (2013.01); **E04F 13/04** (2013.01)

Citation (examination)

FR 2142759 A1 19730202 - POLYPLAC

Cited by

GB2133433A; GB2249564A; US4694626A

Designated contracting state (EPC)

AT BE CH DE FR GB IT NL SE

DOCDB simple family (publication)

EP 0056660 A2 19820728; **EP 0056660 A3 19820818**; **EP 0056660 B1 19850807**; AT E14770 T1 19850815; DE 3070967 D1 19850912; DE 7906824 U1 19790712; DK 103280 A 19800913; EP 0015564 A1 19800917; FI 800644 A 19800913; NO 800371 L 19800915

DOCDB simple family (application)

EP 82100860 A 19800307; AT 82100860 T 19800307; DE 3070967 T 19800307; DE 7906824 U 19790312; DK 103280 A 19800311; EP 80101155 A 19800307; FI 800644 A 19800303; NO 800371 A 19800212