

Title (en)
Electrolytic printing method and apparatus.

Title (de)
Elektrisches Druckverfahren und Vorrichtung.

Title (fr)
Méthode d'impression par électrolyse et appareil.

Publication
EP 0058855 A2 19820901 (EN)

Application
EP 82100837 A 19820205

Priority
US 23756081 A 19810224

Abstract (en)
The recording medium (10) includes three distinct layers: The surface layer (12) incorporates a leuco dye that is responsive to low voltage pulses of amplitude and duration that would be compatible with voltages used by modern integrated circuit chips. The middle layer is a conductive layer and the bottom or support layer is made from any suitable insulating material. The printing apparatus is supplied with write (18) and ground (20) electrodes of predetermined surface area that will contact the recording medium. The spacing or distance of the electrodes along the plane of the recording medium is also predetermined. By proper selection of the thickness of the surface layer (12), the areas of the write and ground electrodes (18, 20) and their lateral spacing, low level electrolytic printing will be assured. A sufficient quantity of current is forced to flow into the surface and conductive layers beneath the write electrode means and thereby effects acceptable printing. Preferably, pulses of no more than 15 V amplitude will cause printing when at least 75 percent of the current delivered will be constrained to flow into the conductive layer (14).

IPC 1-7
B41M 5/20

IPC 8 full level
B41J 2/325 (2006.01); **B41M 5/20** (2006.01)

CPC (source: EP)
B41M 5/20 (2013.01)

Cited by
EP0114303A3; EP0097220B1

Designated contracting state (EPC)
DE FR GB IT

DOCDB simple family (publication)
EP 0058855 A2 19820901; **EP 0058855 A3 19830330**; JP S57140175 A 19820830

DOCDB simple family (application)
EP 82100837 A 19820205; JP 106882 A 19820108