

Title (en)  
REACTIVE ANODE WITH CONSUMPTION INDICATOR AND DIVING CAPSULE FOR A HEAT PROBE

Publication  
**EP 0060289 B1 19860219 (DE)**

Application  
**EP 81902648 A 19810917**

Priority  
DE 3035450 A 19800917

Abstract (en)  
[origin: WO8201017A1] The reactive anode is provided with two contact parts (6, 4) which are accessible from outside, traverse the threaded seal, are isolated from each other and extend into a cavity having plane faces and containing the anode rod or are at least in spatial connection with it. The anode allows with the extremity accessible from outside the connection of an optical or acoustic signalling circuit. The extremity in spatial connection with the cavity of the anode rod acts as an electric switch as soon as the anode rod (10) is consumed. The water of the container enters the cavity, wets or envelopes the contacts (4, 6), thus closing the circuit.

IPC 1-7  
**C23F 13/00; F24H 9/20**

IPC 8 full level  
**C23F 13/02** (2006.01); **C23F 13/22** (2006.01); **F24H 9/20** (2006.01)

CPC (source: EP US)  
**C23F 13/02** (2013.01 - EP); **C23F 13/22** (2013.01 - EP); **F24H 9/2007** (2013.01 - EP US); **F24H 9/45** (2022.01 - EP);  
**F24H 9/455** (2022.01 - EP US)

Cited by  
CN108823571A; DE102006025223A1; DE102006025223B4

Designated contracting state (EPC)  
AT CH FR GB LI NL

DOCDB simple family (publication)  
**WO 8201017 A1 19820401**; DE 3035450 A1 19820429; DE 3035450 C2 19890629; EP 0060289 A1 19820922; EP 0060289 B1 19860219

DOCDB simple family (application)  
**DE 8100148 W 19810917**; DE 3035450 A 19800917; EP 81902648 A 19810917