

Title (en)

Control method for multi-strand rolling mill.

Title (de)

Verfahren der Regelung für ein mehradriges Walzwerk.

Title (fr)

Procédé de réglage d'un laminoir à plusieurs lignes.

Publication

**EP 0061539 A1 19821006 (EN)**

Application

**EP 81301316 A 19810326**

Priority

EP 81301316 A 19810326

Abstract (en)

When two workpiece strands (14, 16) pass through a roll gap between two grooved working rolls (10, 12) on a roll stand to be rolled, the trailing end of one of them may leave the rolls to change the roll gap. At that time screw-down devices (20, 22) on each side of the roll stand are controlled to adjust the roll gap at least at the position of the remaining workpiece. Also in a multi-strand tandem rolling mill, rolling speeds on roll stands upstream of a roll stand from which one of the strands has departed are changed by a speed ratio of  $(1-b_2)/(1-b_1)$  where  $b_1$  and  $b_2$  designate the rates of backward slips in the presence of the two strands and in the absence of one of the strands on the last-mentioned roll stand. Alternatively roll speeds on roll stands downstream of that roll stand may be changed by a speed ratio of  $(1+f_2)/(1+f_1)$  where  $f_1$  and  $f_2$  designate the rates of forward slip which correspond to the  $b_1$  and  $b_2$  respectively.

IPC 1-7

**B21B 37/12**

IPC 8 full level

**B21B 37/16** (2006.01); **B21B 1/18** (2006.01); **B21B 13/00** (2006.01); **B21B 13/02** (2006.01)

CPC (source: EP)

**B21B 37/165** (2013.01); **B21B 1/18** (2013.01); **B21B 13/02** (2013.01); **B21B 2013/006** (2013.01)

Citation (search report)

- DE 1143263 C
- DE 1150144 C
- US 2933956 A 19600426 - SNOW RICHARD R
- DE 1427959 A1 19681128 - MORGAN CONSTRUCTION CO

Cited by

CN103658193A; US11033910B2; WO2018039719A1

Designated contracting state (EPC)

DE FR GB

DOCDB simple family (publication)

**EP 0061539 A1 19821006; EP 0061539 B1 19850206**; DE 3168723 D1 19850321

DOCDB simple family (application)

**EP 81301316 A 19810326**; DE 3168723 T 19810326