

Title (en)
GLASS COATED DISK THERMISTOR

Publication
EP 0061550 A3 19831005 (EN)

Application
EP 81304781 A 19811014

Priority
US 19699180 A 19801014

Abstract (en)
[origin: EP0061550A2] A tri-metal contact film (31, 33) of silver, platinum, and palladium is metallurgically bonded to the opposite surfaces of a disk (11) of dense, controlled temperature coefficient of resistance thermistor material. The disk is trimmed to the desired electrical dimensions and a silver-clad wire (61, 63) is fusion welded by thermal compression bonding to the contact film (31, 33) on each side of the disk. The method of making electrical contact allows the assembly to be encased in a conformal glass coating (75). The glass coating (75) provides an enhanced stability thermistor having predetermined characteristics.

IPC 1-7
H01C 7/04; H01C 1/142; G01K 7/22; H01C 7/02

IPC 8 full level
H01C 7/04 (2006.01)

CPC (source: EP)
H01C 7/04 (2013.01)

Citation (search report)
• [A] GB 1257148 A 19711215
• [A] GB 685229 A 19521231 - WESTERN ELECTRIC CO
• [A] GB 770175 A 19570320 - WELWYN ELECTRICAL LAB LTD, et al

Cited by
US5142267A; CN114291783A; AT398636B; CN105890794A; CN106092364A; EP0171877A1; EP0111361A1; US4533898A; EP0400167B1

Designated contracting state (EPC)
DE FR GB SE

DOCDB simple family (publication)
EP 0061550 A2 19821006; **EP 0061550 A3 19831005**; CA 1175954 A 19841009; JP S5799703 A 19820621

DOCDB simple family (application)
EP 81304781 A 19811014; CA 387641 A 19811009; JP 16404981 A 19811014