

Title (en)  
CLAMPING CONTACT

Publication  
**EP 0063206 B1 19851002 (DE)**

Application  
**EP 82100506 A 19820126**

Priority  
DE 3115434 A 19810416

Abstract (en)  
[origin: EP0063206A2] 1. Clamping contact of an electrical connector, having two contact tongues (13) arranged adjacent to each other, which form a slot (15) between them for the contacting clamping of a conductor, are cut out of the base (5) of the electrical connector, are bent approximately at right angles to the base (5), and abut at the sides against lateral walls (7) of the connector, the slot (15) being slightly narrower than the bare conductor and the contact edges (17) being sharp in order to cut into the insulation of an insulated conductor which is pressed into the slot (15), and a widening being provided in the insertion region of the slot (15), characterised in that the slot (15) which extends between the contact tongues (13) becomes a cut-away portion (14) in the base (5).

IPC 1-7  
**H01R 4/24**

IPC 8 full level  
**H01R 4/24** (2006.01)

CPC (source: EP)  
**H01R 4/2466** (2013.01)

Cited by  
US6796830B2; EP1251589A1; EP0372767A1; EP0355702A3; EP0304066A1

Designated contracting state (EPC)  
FR GB IT NL

DOCDB simple family (publication)  
**EP 0063206 A2 19821027; EP 0063206 A3 19830817; EP 0063206 B1 19851002; DE 3115434 A1 19821111**

DOCDB simple family (application)  
**EP 82100506 A 19820126; DE 3115434 A 19810416**