

Title (en)

Plug insert elements for flat cables.

Title (de)

Steckereinsatzelemente für Flachschnüre.

Title (fr)

Unités de fiche d'insertion pour câbles plats.

Publication

EP 0063696 A1 19821103 (DE)

Application

EP 82102536 A 19820326

Priority

DE 3112362 A 19810328

Abstract (en)

1. Plug insert element for flat cables for insertion in a plug casing, in particular for connection to flat cables in signal engineering, comprising a block-shaped insulating portion (2) with mounting guides (4) closed on one end and provided within the said insulating portion (2) in a row one beside the other for receiving the ends of the individual conductors (3) of the flat cables, each of the said mounting guides (4) being engaged by a contact reed (5) which can be pushed through the insulation of the individual conductors (3) to establish electric contact with the strand (7) of the associated individual conductor (3), characterized in that the contact reeds (5) take the form of laterally bent-off portions of elongated contact springs (12) and that the contact springs (12) are provided in diametrically opposite arrangement on two parallel outer faces (8, 9) of the block-shaped insulating portion (2) so that the contact reeds (5) project into the mounting guides (4) alternately from opposite sides (8, 9) of the block-shaped insulating portion (2).

Abstract (de)

Mit der vorliegenden Erfindung wird ein Steckereinsatzelement beschrieben, das zur Aufnahme von Einzeladern von Flachschnüren dient und insbesondere zur Anbindung an Flachschnüre der Schwachstromtechnik verwendet werden kann. Das erfindungsgemäße Steckereinsatzelement zeichnet sich gegenüber den bekannten Bauarten dadurch aus, daß die in einen Isolierblock eingeführten Einzeladern abwechselnd von zwei sich gegenüberliegenden Seiten des Blockbereiches kontaktiert werden, so daß zwei gegenüberliegende Außenflächen des Isolierblocks zur Anordnung der Kontaktfedern ausgenutzt werden können. Bei gleichbleibender Isolierblockgröße können mehr Einzeladern einer Flachschnur kontaktiert werden, als dies bei bekannten Bauarten der Fall ist. Ebenso brauchen keine vergoldeten Kontakte verwendet zu werden, da die Leitungsquerschnitte groß genug sind, um eine einwandfreie Kontaktgabe zu erhalten.

IPC 1-7

H01R 13/26; H01R 9/07; H01R 4/24

IPC 8 full level

H01R 4/24 (2006.01); **H01R 12/67** (2011.01); **H01R 13/26** (2006.01)

CPC (source: EP US)

H01R 4/2404 (2013.01 - EP US); **H01R 12/67** (2013.01 - EP US); **H01R 13/26** (2013.01 - EP)

Citation (search report)

- [AD] DE 2432122 A1 19750123 - WESTERN ELECTRIC CO
- [A] DE 2224326 A1 19721207 - AMP INC
- [A] CH 413034 A 19660515 - BURNDY CORP [US]
- [A] US 3982809 A 19760928 - WARD RONALD C, et al

Cited by

EP0795931A1; EP0141091A3; US4602830A; EP0358404A3; EP0263654A3; EP0227153A1; US4715824A; US4749361A; WO8601946A1

Designated contracting state (EPC)

AT BE CH DE FR GB IT LU NL SE

DOCDB simple family (publication)

EP 0063696 A1 19821103; EP 0063696 B1 19850710; AT E14260 T1 19850715; DE 3112362 A1 19821014; DE 3112362 C2 19840809;
DE 3264632 D1 19850814

DOCDB simple family (application)

EP 82102536 A 19820326; AT 82102536 T 19820326; DE 3112362 A 19810328; DE 3264632 T 19820326