

Title (en)
X-RAYS MULTIDETECTOR

Publication
EP 0064913 B1 19860402 (FR)

Application
EP 82400769 A 19820428

Priority
FR 8109000 A 19810506

Abstract (en)
[origin: US4481420A] The invention relates to a process for making a multidetector of X-rays forming a plane beam. This multidetector comprises a tight chamber filled with an ionizable gas and, in this chamber, at least one main multidetector assembly comprising a plane conducting plate, electrically insulated from the chamber and a plurality of flat electrodes parallel to the plate, insulated from this plate. This process is characterized in that it consists in making the electrodes, as well as main connections between these electrodes and measuring points outside the chamber enabling the currents circulating respectively in these electrodes to be sampled, on a main face of an electrically insulating plate, these main connections being electrically insulated from the chamber and passing therethrough in tight manner, opposite the source which emits the X-rays. The invention is more particularly applicable to X-ray multidetectors intended for the tomography or radiography of organs or for checking baggage.

IPC 1-7
H01J 47/02; A61B 6/02

IPC 8 full level
G01N 23/04 (2006.01); **A61B 6/00** (2006.01); **G01T 1/185** (2006.01); **H01J 47/02** (2006.01)

CPC (source: EP US)
H01J 47/02 (2013.01 - EP US)

Cited by
EP0063705A3; FR2594960A1; FR2570908A1; GB2189932A; GB2187328A; GB2187328B; EP0326479A1; FR2626379A1; US4912736A

Designated contracting state (EPC)
DE GB NL

DOCDB simple family (publication)
EP 0064913 A2 19821117; EP 0064913 A3 19830803; EP 0064913 B1 19860402; DE 3270211 D1 19860507; FR 2505492 A1 19821112;
FR 2505492 B1 19851108; JP S57187679 A 19821118; US 4481420 A 19841106

DOCDB simple family (application)
EP 82400769 A 19820428; DE 3270211 T 19820428; FR 8109000 A 19810506; JP 7468682 A 19820506; US 37061482 A 19820422