

Title (en)  
Cancellor.

Title (de)  
Entwerter.

Title (fr)  
Dispositif pour annuler.

Publication  
**EP 0064963 A1 19821117 (EN)**

Application  
**EP 82850100 A 19820505**

Priority  
SE 8102805 A 19810505

Abstract (en)  
A cancellor for tickets or the like comprising a number of wheels (8) being rotatably mounted on a common shaft (7) and individually settable in locked positions (10) each corresponding to a position of types disposed on the wheels for the printing of characters on a ticket or the like. Each wheel (8) has in each locked position (10) at least one zero position (17) corresponding to said locked position. The zero positions of each wheel are located at the same distance from the centre of the wheel. Each zero position in the respective locked position permits free passage for a sensing means (18,19). Furthermore, for determining the position of each wheel, a code position (20, 21) is disposed on the wheel between each pair of adjacent zero positions, so that when rotating the wheel to be set between two adjacent locked positions, one of said code positions (20, 21) passes by said sensing means.

IPC 1-7  
**B41J 7/34**; **B41K 3/08**; **G07B 11/02**

IPC 8 full level  
**B41J 7/34** (2006.01); **B41K 3/08** (2006.01); **G07B 11/02** (2006.01)

CPC (source: EP)  
**B41J 7/34** (2013.01); **B41K 3/08** (2013.01); **G07B 11/02** (2013.01)

Citation (search report)  
• [Y] US 3399297 A 19680827 - MILLER ROBERT L  
• [Y] US 3015265 A 19620102 - PAUL GMEINER  
• [A] GB 2018684 A 19791024 - MCCORQUODALE MACHINE SYSTEMS L  
• [A] US 3747517 A 19730724 - ROBACZEK E  
• [A] US 3929276 A 19751230 - LUNDSTROM GORAN INGEMAR, et al

Cited by  
FR2625138A1; US4852482A; EP0181804A1; FR2572827A1; US4723486A

Designated contracting state (EPC)  
BE CH DE FR GB LI NL

DOCDB simple family (publication)  
**EP 0064963 A1 19821117**; **EP 0064963 B1 19861001**; DE 3273518 D1 19861106; ES 511940 A0 19830216; ES 8304335 A1 19830216; SE 8102805 L 19821106

DOCDB simple family (application)  
**EP 82850100 A 19820505**; DE 3273518 T 19820505; ES 511940 A 19820505; SE 8102805 A 19810505