

Title (en)
SYSTEM FOR ELECTRONIC IDENTIFICATION

Publication
EP 0065181 B1 19880727 (FR)

Application
EP 82103814 A 19820504

Priority
FR 8109453 A 19810512

Abstract (en)
[origin: ES8304345A1] The identification system consists of a key comprising a passive memory area (10) and a shift register (9) and a lock which can be coupled with the key. The lock is capable of supplying a set number of pulses causing the code contained in the memory (10) to be loaded into the register (9). The register (9) is subdivided into a certain number of elements linked together but loaded independently. This loading is carried out successively by the multiplexer (111). Transmission of an incorrect number of loading pulses leads, through connection (113), to a modification of the contents of the shift register (9).

IPC 1-7
G07F 7/08; **E05B 49/00**

IPC 8 full level
E05B 49/00 (2006.01); **G06K 17/00** (2006.01); **G07C 9/00** (2006.01); **G07F 7/08** (2006.01); **G07F 7/12** (2006.01)

CPC (source: EP US)
G07C 9/00174 (2013.01 - EP US); **G07F 7/086** (2013.01 - EP US)

Citation (examination)
FR 2136269 A5 19721222 - EASTERN CO

Cited by
ES2080633A1

Designated contracting state (EPC)
AT BE CH DE GB IT LI LU NL SE

DOCDB simple family (publication)
EP 0065181 A2 19821124; **EP 0065181 A3 19830406**; **EP 0065181 B1 19880727**; AT E36085 T1 19880815; CA 1187992 A 19850528; DE 3278830 D1 19880901; ES 512059 A0 19830216; ES 8304345 A1 19830216; FR 2506048 A1 19821119; FR 2506048 B1 19860207; JP H0418355 B2 19920327; JP S5824073 A 19830212; US 4481513 A 19841106

DOCDB simple family (application)
EP 82103814 A 19820504; AT 82103814 T 19820504; CA 402758 A 19820511; DE 3278830 T 19820504; ES 512059 A 19820511; FR 8109453 A 19810512; JP 8082482 A 19820512; US 37731182 A 19820512