

Title (en)

A method of repair of a coke-oven battery, and a panel for use in the method.

Title (de)

Verfahren zur Reparatur einer Koksofenbatterie und dazu verwendbare Wand.

Title (fr)

Procédé de réparation d'une batterie de fours à coke et paroi pour la mise en oeuvre du procédé.

Publication

EP 0065328 A2 19821124 (EN)

Application

EP 82200525 A 19820503

Priority

NL 8102281 A 19810511

Abstract (en)

A coke oven battery is repaired, during operation, by creating a screened-off working space which extends over at least part of one or more coking chambers. To this end, insulating material is applied against the side-walls of the chamber or chambers so that they remain at a relatively high temperature, to reduce the risk of crack formation on cooling. Repair is effected from the screened-off space. To improve the working conditions in this space, in particular to reduce the temperature to near room temperature, the insulation includes one or more panels which have a layer of insulating material and ducts through which cooling fluid, e.g. water, is passed.

IPC 1-7

C10B 29/06; F27D 1/16

IPC 8 full level

C10B 29/06 (2006.01); **F27D 1/16** (2006.01); **F27B 13/06** (2006.01); **F27D 21/00** (2006.01)

CPC (source: EP)

C10B 29/06 (2013.01); **F27D 1/16** (2013.01); **F27B 13/06** (2013.01); **F27D 2001/161** (2013.01); **F27D 2021/0057** (2013.01)

Cited by

US4921579A; US6539602B1; EP0421147A1

Designated contracting state (EPC)

BE DE FR GB IT NL

DOCDB simple family (publication)

EP 0065328 A2 19821124; EP 0065328 A3 19830518; EP 0065328 B1 19850724; CA 1218332 A 19870224; DE 3264884 D1 19850829;
NL 8102281 A 19821201

DOCDB simple family (application)

EP 82200525 A 19820503; CA 402505 A 19820507; DE 3264884 T 19820503; NL 8102281 A 19810511