

Title (en)  
METHOD AND APPARAUS FOR FORMING WORDS OF PRINTED CHARACTERS

Publication  
**EP 0066460 B1 19840926 (EN)**

Application  
**EP 82302738 A 19820527**

Priority  
US 26816381 A 19810529

Abstract (en)  
[origin: EP0066460A2] A method and apparatus are disclosed for use in forming words on tape, useful e.g. as labels, from sheets bearing printed, transferable characters, e.g. a set of printed alphabets. A tape dispenser (32) containing a roll of a transparent adhesive tape (34) includes a frame (40) defining a rectangular window (42) which can be positioned horizontally and vertically at any place over the character sheet (20). When it is desired to transfer a selected letter to the tape, the user presses the selected area of the tape against the letter. Because of the tacky adhesive on the tape, when pressure is removed, the selected letter is lifted from the indicia sheet and transferred to the tape. The process is repeated as often as necessary to form the desired word. The strip of tape on which the word has been formed is then severed from the roll and adhered to any desired receiving surface by means of the tacky adhesive on the tape. Accurate base-line adjustment of the characters forming the word is provided by means of an indexing mechanism which enables the tape dispenser (32) to move vertically within a slide (18) to fixed positions exactly correlating to the rows of printed characters on the sheet (20).

IPC 1-7  
**B44C 1/16**

IPC 8 full level  
**B41F 17/00** (2006.01); **B41J 2/385** (2006.01); **B41J 7/32** (2006.01); **B44C 1/16** (2006.01)

CPC (source: EP)  
**B44C 1/162** (2013.01)

Cited by  
FR2579524A1; WO9113805A1

Designated contracting state (EPC)  
AT BE CH DE FR GB IT LI LU NL SE

DOCDB simple family (publication)  
**EP 0066460 A2 19821208; EP 0066460 A3 19830413; EP 0066460 B1 19840926**; AT E9563 T1 19841015; CA 1171393 A 19840724; DE 3260828 D1 19841031; JP S5829672 A 19830221

DOCDB simple family (application)  
**EP 82302738 A 19820527**; AT 82302738 T 19820527; CA 403960 A 19820528; DE 3260828 T 19820527; JP 9002382 A 19820528