

Title (en)
DOOR LOCK

Publication
EP 0066535 B1 19850814 (FR)

Application
EP 82810203 A 19820514

Priority
CH 319281 A 19810515

Abstract (en)
[origin: ES8305455A1] A keeper for a bolt having a catch (4) and a housing (27, 28) which presents two internal faces provided with grooves (29). These grooves (29) form an angle with the direction according to which the bolt of the lock moves. A runner (30) carries on two opposite sides forms (31) corresponding to the grooves (29) and sliding in the latter. This runner (30) presents an opening (33) intended to give way to the bolt, one edge (34) of which forms a supporting side for this bolt. Two adjusting screws (32) allow adjustment of the position of the runner (30) with respect to the housing (27, 28) while 4 screws (36) connecting plaques (34, 35) leaning on the housing (27,28) allowing the blocking of the runner (30) with respect to this housing.

IPC 1-7
E05B 15/02

IPC 8 full level
E05B 63/00 (2006.01); **E05B 15/02** (2006.01)

CPC (source: EP US)
E05B 15/025 (2013.01 - EP US); **Y10T 292/705** (2015.04 - EP US)

Citation (examination)
CH 493725 A 19700715 - PARLIER ROGER [CH]

Designated contracting state (EPC)
AT BE DE FR GB IT LU NL SE

DOCDB simple family (publication)
EP 0066535 A2 19821208; EP 0066535 A3 19830427; EP 0066535 B1 19850814; AT E14909 T1 19850815; AU 8327382 A 19821118; BR 8202773 A 19830419; CA 1193634 A 19850917; CH 644930 A5 19840831; DE 3265394 D1 19850919; ES 512180 A0 19830401; ES 8305455 A1 19830401; JP S5824074 A 19830212; PT 74853 A 19820601; PT 74853 B 19831122; US 4480864 A 19841106

DOCDB simple family (application)
EP 82810203 A 19820514; AT 82810203 T 19820514; AU 8327382 A 19820504; BR 8202773 A 19820513; CA 403033 A 19820514; CH 319281 A 19810515; DE 3265394 T 19820514; ES 512180 A 19820514; JP 8087482 A 19820515; PT 7485382 A 19820506; US 37696982 A 19820511