

Title (en)
CORK-SCREW

Publication
EP 0068069 B1 19860212 (DE)

Application
EP 82101417 A 19820225

Priority
DE 8118315 U 19810624

Abstract (en)
[origin: EP0068069A1] 1. Corkscrew (10) having a bell (12) with a pot portion (34) at its lower end (30), including a spindle (16) which is borne in the neck (14) of the bell, is apt to be turned at its top by means of a handle (18) and extends downward by way of a screw (26), including cork ejecting means by way of at least two ribs (52) opposite to each other and running conically towards each other in the bell from the pot portion to the neck, and including a centering piece (36) in the pot portion, wherein a resilient thrust ring (32) is countersunk in the centering piece (36), wherein a resilient guide ring (58) having recesses (60) that are at least approximately parallel to the axis is joined to the thrust ring and wherein the point (56) of the screw (26) in its topmost position ends at about the level of the upper edge (54) of the thrust ring or above.

IPC 1-7
B67B 7/04

IPC 8 full level
B67B 7/04 (2006.01)

CPC (source: EP)
B67B 7/0441 (2013.01)

Cited by
CN1043985C; FR2639629A1; US4836060A; GB2504142A; GB2246341A; GB2246341B; EP0928771A1; FR2669320A1; WO9208668A1

Designated contracting state (EPC)
BE DE FR GB IT NL

DOCDB simple family (publication)
EP 0068069 A1 19830105; EP 0068069 B1 19860212; BE 905945 Q 19870416; DE 3269033 D1 19860327; DE 8118315 U1 19821209

DOCDB simple family (application)
EP 82101417 A 19820225; BE 2061124 A 19861217; DE 3269033 T 19820225; DE 8118315 U 19810624