

Title (en)

Method of making a cellulosic fibre pulp for non paperlike applications.

Title (de)

Verfahren zur Herstellung eines Cellulosefaserstoffbreis für nicht papierähnliche Anwendungen.

Title (fr)

Procédé de fabrication d'une pâte de fibres cellulosique pour utilisation non papetière.

Publication

**EP 0070782 A1 19830126 (FR)**

Application

**EP 82401346 A 19820720**

Priority

FR 8114054 A 19810720

Abstract (en)

1. Process for producing a pulp of cellulose fibres not to be used for paper-making, by passing wood chips into a pulping machine comprising at least two screws (1, 2) having identical threads meshing in one another and driven in rotation on the inside of a sleeve (3) provided with an upstream chip inflow orifice (31) and with a downstream pulped-material cutflow orifice (32), the threads (11, 21) of the screws (1, 2) having varied pitches determining a succession of processing zones (I, II etc.), each comprising a section (A) with a direct pitch for driving the material downstream and a section (B) with a reversed pitch for increasing pressure as a result of the braking of the material, the threads with reverse pitches being provided with apertures (12, 22) for the downstream passage of the material which has reached the desired degree of pulping, the sleeve (3) being provided with filtering parts (34) located upstream of the reverse-pitch braking sections (B), at least in the first two processing zones (I, II), in order to carry out drying of the material, characterised in that the material is first brought to the desired degree of pulping by being passed through the first processing zones (I, II, III), which incorporate reverse-pitch sections (B) provided with apertures, the width of which decreases from one zone to the next to a width of the order of 4 to 5 mm, in that, at the same time, drying together with filtration is carried out to a degree of dryness of between 35% and 55%, and in that the shives and clusters of fibres are subsequently eliminated in the same machine, without reducing the length of the fibres and without carrying out any fibrillation, by passing the pulped and dried material through at least two additional processing zones (IV, V), which incorporate reverse-pitch braking sections provided with apertures having the same width of the order of 4 to 5 mm as in the last pulping zone (III), and a homogenous pulp consisting solely of isolated fibres which have not undergone any fibrillation is obtained at the outlet of the machine.

Abstract (fr)

Procédé de fabrication d'une pâte de fibres cellulosique par passage de copeaux de bois dans une machine de défibrage à au moins deux vis (1, 2) à filets identiques à pas variés engranant l'une dans l'autre en rotation à l'intérieur d'un fourreau (3). Après avoir obtenu le degré de défibrage souhaité dans les premières zones de traitement (I, II, III), on élimine les buchettes et amas de fibres par passage dans au moins deux zones supplémentaires (IV, V) jusqu'à obtention d'une pâte homogène de fibres isolées sans fibrillation. L'invention s'applique à la fabrication de pâtes de fibres cellulosiques pour usages non papetiers.

IPC 1-7

**D21B 1/30**

IPC 8 full level

**D21B 1/30** (2006.01)

CPC (source: EP)

**B30B 11/243** (2013.01); **B30B 11/246** (2013.01); **D21B 1/30** (2013.01)

Citation (search report)

- [A] FR 2436844 A2 19800418 - CREUSOT LOIRE
- [A] FR 2451963 A1 19801017 - CREUSOT LOIRE

Cited by

CN107541977A; EP0324689A1; FR2625645A1; FR2980332A1; GB2511647A; GB2511647B; EP0979895A1; FR2980333A1; GB2511648A; GB2511648B; US8777144B2; US8783591B2; WO8906488A1; WO2013057402A1; WO2013045820A1

Designated contracting state (EPC)

AT BE CH DE FR GB IT LI LU NL SE

DOCDB simple family (publication)

**EP 0070782 A1 19830126; EP 0070782 B1 19851002**; AT E15918 T1 19851015; CA 1193405 A 19850917; DE 3266691 D1 19851107; FR 2509766 A1 19830121; FR 2509766 B1 19831110

DOCDB simple family (application)

**EP 82401346 A 19820720**; AT 82401346 T 19820720; CA 404787 A 19820609; DE 3266691 T 19820720; FR 8114054 A 19810720