

Title (en)
FUSE

Publication
EP 0073201 B1 19860226 (FR)

Application
EP 81903232 A 19811123

Priority
FR 8024971 A 19801125

Abstract (en)
[origin: WO8201961A1] The fuse comprises an elongated support formed by at least partially ferrite, magnetised in the direction of its thickness and on which there is arranged, between two terminals, a metal wire (9) capable of being destroyed by fusion. The fuse comprises for example two ferrite strips (5 and 6) assembled and maintained in a spaced relationship by two insulating material bars (7 and 8), a silver wire (9) being arranged between the two strips. During fusion of the wire, the melting metal and the electric arc are expelled sideways according to Laplace law.

IPC 1-7
H01H 85/38

IPC 8 full level
H01H 37/76 (2006.01); **H01H 85/00** (2006.01); **H01H 85/06** (2006.01); **H01H 85/08** (2006.01); **H01H 85/38** (2006.01)

CPC (source: EP US)
H01H 85/38 (2013.01 - EP US); **H01H 2085/386** (2013.01 - EP US)

Cited by
DE102012207912A1; DE102013208656B4; DE102013022355B3; DE102012207912B4; DE202012012570U1; DE102013208656A1

Designated contracting state (EPC)
AT CH DE FR GB LI LU NL SE

DOCDB simple family (publication)
WO 8201961 A1 19820610; BE 891223 A 19820316; CA 1171442 A 19840724; DK 147089 B 19840402; DK 147089 C 19840910; DK 330682 A 19820723; EP 0073201 A1 19830309; EP 0073201 B1 19860226; ES 508011 A0 19821116; ES 8301064 A1 19821116; FR 2494901 A1 19820528; FR 2494901 B1 19830225; IT 1139838 B 19860924; IT 8125263 A0 19811124; JP H0117216 B2 19890329; JP S57501902 A 19821021; SU 1170979 A3 19850730; US 4514716 A 19850430

DOCDB simple family (application)
FR 8100152 W 19811123; BE 206632 A 19811123; CA 390925 A 19811125; DK 330682 A 19820723; EP 81903232 A 19811123; ES 508011 A 19811125; FR 8024971 A 19801125; IT 2526381 A 19811124; JP 50367381 A 19811123; SU 3524756 A 19821223; US 40363482 A 19820720