

Title (en)

APPARATUS FOR TEARING A SECTION FROM A WEB IN PARALLEL WITH THE WEFT THREADS

Publication

EP 0075075 B1 19860723 (DE)

Application

EP 82105560 A 19820624

Priority

DE 8127224 U 19810917

Abstract (en)

[origin: ES8305868A1] Equipment for severing a segment from a length of fabric in a thread-adjusted manner has a bench with spaced first and second sides. A clamping system is mounted to the first side for releaseably clamping a first edge of the fabric. A carriage is displaceably mounted to the bench and is adapted for being displaced from the first to the second side. First and second adjacently disposed rotatable rollers are mounted to the carriage for engaging and ripping the fabric. A cylinder and piston system for displacing the carriage is mounted to the bench.

IPC 1-7

D06H 7/20

IPC 8 full level

D06H 7/14 (2006.01); **D06H 7/16** (2006.01); **D06H 7/20** (2006.01)

CPC (source: EP US)

D06H 7/20 (2013.01 - EP US); **Y10T 225/314** (2015.04 - EP US); **Y10T 225/386** (2015.04 - EP US); **Y10T 225/393** (2015.04 - EP US)

Cited by

US5168219A

Designated contracting state (EPC)

AT BE CH DE FR GB IT LI NL SE

DOCDB simple family (publication)

EP 0075075 A2 19830330; **EP 0075075 A3 19840530**; **EP 0075075 B1 19860723**; AT E20917 T1 19860815; CA 1181045 A 19850115; DE 3272133 D1 19860828; DE 8127224 U1 19820211; ES 515770 A0 19830501; ES 8305868 A1 19830501; JP S5860058 A 19830409; JP S6225786 B2 19870604; US 4453658 A 19840612; ZA 826434 B 19830727

DOCDB simple family (application)

EP 82105560 A 19820624; AT 82105560 T 19820624; CA 410823 A 19820903; DE 3272133 T 19820624; DE 8127224 U 19810917; ES 515770 A 19820916; JP 16106782 A 19820917; US 40917582 A 19820818; ZA 826434 A 19820902