

Title (en)

Door actuating apparatus with an opening security.

Title (de)

Torantriebsgerät mit Öffnungssicherung.

Title (fr)

Appareil de commande pour porte comprenant une sécurité d'ouverture.

Publication

EP 0075269 A1 19830330 (DE)

Application

EP 82108510 A 19820915

Priority

DE 3137501 A 19810921

Abstract (en)

1. A door actuating device having a motor-driven entrainment member (7) which is moved, in a specific path (3), forwards for the opening of a door leaf and back for its closing and which is coupled to a coupling member (5), connected to the door leaf to be moved, for reciprocating displacement in relation to this through a specific displacement distance (14) in the direction of the path (3) between a closing position (20) and an opening position (17) and which is in driving connection (12, 13), through an approach ramp (13) extending obliquely to the direction of the path (3), with a locking bolt (11) held on the coupling member (5), which locking bolt is transferred, controlled through this connection and transversely to the direction of the path (3), in the closing position (20) of the entrainment member (7) into a locking position (22) against a stop (21) fixed to the frame of the device and in the opening position (17) of the entrainment member (7) into an unlocking position (23) away from the stop (21), the entrainment member (7) comprising a recess (10) which defines the displacement distance (14) and in which there engages an entrainment block (9) which is held on the coupling member (5) and which forms a switching member with the locking bolt (11), the coupling between the entrainment member (7) and the coupling member (5) being able to be completely cancelled by hand by actuation of an entrainment element displaceable transversely to the direction of the path (3), characterised in that the entrainment member (7) is rigidly connected directly to the drive member (2) of the door drive, which member is moved in the direction of the path (3), and that the entrainment block (9) engaging in the upwardly open recess (10) in the entrainment member (7) is mounted as an entrainment element on the coupling member (5) for displacement between a position of engagement in the recess (10) and a position out of engagement with this recess (10) and has a mechanical coupling (25) to the locking bolt (11) over this displacement distance.

Abstract (de)

Bei einem Torantriebsgerät mit einem motorgetriebenen, in einer bestimmten Bahn für die Öffnung eines Torblattes hin und dessen Schließen zurück bewegten Mitnehmerteil (7) und mit einem Kupplungssteil (5), das an das Mitnehmerteil (7) angekuppelt und mit dem zu bewegenden Torblatt verbunden ist, wird zur Sicherung gegen unbefugtes Öffnen des Torblattes bei stehendem Antrieb und der Aufhebung dieser Sicherung bei normaler Torblattbewegung vom Antrieb her vorgeschlagen, das Mitnehmerteil (7) relativ zu dem Kupplungssteil (5) in Richtung der Bahn (3) um eine bestimmte Verschiebestrecke (14) zwischen einer Schließstellung und einer Öffnungsstellung hin- und herverschiebbar auszubilden und mit einem an dem Kupplungssteil (5) gehaltenen Umschaltteil (8) getrieblich zu verbinden, welches über diese Verbindung (12, 13) gesteuert in Schließstellung des Mitnehmerteils (7) in eine Verriegelungsstellung an einem gerätekassisfesten Anschlag (21) und in der Öffnungsstellung des Mitnehmerteils (7) in eine Entriegelungsstellung von dem Anschlag (21) entfernt versetzt ist.

IPC 1-7

E05F 15/10

IPC 8 full level

E05F 15/10 (2006.01); **E05F 15/668** (2015.01); **E05D 11/00** (2006.01)

CPC (source: EP)

E05F 15/668 (2015.01); **E05D 11/0018** (2013.01); **E05Y 2201/214** (2013.01); **E05Y 2201/244** (2013.01); **E05Y 2900/106** (2013.01)

Citation (search report)

- [X] FR 2349014 A1 19771118 - ROI RENE [FR]
- [X] US 3909980 A 19751007 - COURTNEY WILLIAM B, et al
- [A] DE 2741539 A1 19790329 - RIEKINGER FAVORIT TUEREN

Cited by

EP0329039A1; EP1083287A3

Designated contracting state (EPC)

AT BE CH DE FR GB IT LI LU NL SE

DOCDB simple family (publication)

EP 0075269 A1 19830330; **EP 0075269 B1 19860226**; AT E18279 T1 19860315; DE 3137501 A1 19830414; DE 3137501 C2 19860213;
DE 3269412 D1 19860403

DOCDB simple family (application)

EP 82108510 A 19820915; AT 82108510 T 19820915; DE 3137501 A 19810921; DE 3269412 T 19820915