

Title (en)
METHOD AND INSTALLATION FOR CHECKING INSTALLED CARBURETORS

Publication
EP 0076178 B1 19861210 (FR)

Application
EP 82401520 A 19820811

Priority
FR 8118484 A 19810930

Abstract (en)
[origin: ES8305466A1] For determining the amount of wear of the movable parts of a carburetor, the throttle of the carburetor is retained in a position where it defines a predetermined cross-sectional flow area with the whole of the induction passage. That predetermined area is the area for which, when the carburetor was new, the edge of the throttle was midway along the bypass aperture of the idling circuit. The degree of vacuum in the idling circuit of the carburetor is then compared with a reference value which is the degree of vacuum which prevails on the carburetor in brand new condition under the same operating conditions.

IPC 1-7
F02M 19/01

IPC 8 full level
F02M 19/01 (2006.01)

CPC (source: EP US)
F02M 19/01 (2013.01 - EP US)

Cited by
CN111677601A; RU2484112C2

Designated contracting state (EPC)
DE FR GB IT

DOCDB simple family (publication)
EP 0076178 A2 19830406; EP 0076178 A3 19831207; EP 0076178 B1 19861210; DE 3274668 D1 19870122; ES 515660 A0 19830501; ES 8305466 A1 19830501; FR 2513698 A1 19830401; FR 2513698 B1 19840113; JP H0341674 B2 19910624; JP S5870041 A 19830426; PT 75457 A 19820901; PT 75457 B 19841023; US 4483186 A 19841120

DOCDB simple family (application)
EP 82401520 A 19820811; DE 3274668 T 19820811; ES 515660 A 19820911; FR 8118484 A 19810930; JP 17248182 A 19820930; PT 7545782 A 19820824; US 42035082 A 19820920