

Title (en)

DEVICE FOR FORMING AND DELIVERING SMALL PACKAGES CONSISTING OF SEVERAL PLAIN INDIVIDUAL PRODUCTS OF PAPER, CELLULOSE WADDING OR THE LIKE

Publication

**EP 0076939 B1 19860226 (DE)**

Application

**EP 82108652 A 19820918**

Priority

- DE 3140021 A 19811008
- DE 3220130 A 19820528

Abstract (en)

[origin: EP0076939A1] 1. A device for forming packages consisting of several plain individual products of paper, cellulose wadding or the like, and for delivering said packages in a rapid sequence, said individual products (A) being conveyed at intervals by a belt conveyer system (1-2-3) to a stacking mechanism (B-C, D-E), and the packages (P) formed therein being removed and led away by a delivery mechanism (17) following said stacking mechanism, whereby two stacking mechanisms (B-C, D-E) are arranged one after the other in feeding direction, said stacking mechanisms operating in alternating sequence and the conveyance of the products to the second stacking mechanism (D-E) taking place straight through the first stacking mechanism (B-C), whereby each of the stacking mechanisms comprises a collecting cassette (C-E) arranged below the belt conveyer system, as well as an expeller mechanism (B, D) arranged above the belt conveyer system (1-2-3) and including a vertically operating expeller plate (25), said belt conveyer system (1-2-3) comprising, at least in the range of the expeller mechanisms (B, D), parallelly moving individual belts (1-2) which are arranged in such a way that the products (A) are grasped in narrow marginal zones and are pushed, by one of the expeller mechanisms (B, D), through the belt conveyer system (1-2-3) into one of the collecting cassettes (C-E), the delivery mechanism (17) being arranged relative to the stacking mechanisms (B-C, D-E) in such a way that the delivery mechanism takes place in a direction perpendicularly to the direction of feed (Z), characterized in that each of the expeller mechanisms (B, D) comprises a movable lifting frame (4) which slides in rod guides (5) and at the lower end of which at least one expeller plate (25, 25a) is provided, and which is adapted to be lifted, against the force of a compression spring (8), by means of an eccentric sheave (6) secured to a drive shaft (10), and that, during the operation of the second stacking mechanism (D), the expeller mechanism (B) of the first stacking mechanism is blocked by a locking mechanism comprising a driveable hollow control shaft (9) enclosing the drive shaft (10) over part of its length to which control shaft a cam plate (11) is attached the circumference of which comprises two angle areas having radii of different length, and further comprising a stop member (14) attached to the lifting frame (4), said stop member being guided on the circumference of the cam plate (11) in such a manner that, depending on the position of the cam plate, the lifting frame (4) is either held back in its raised-position or is released.

IPC 1-7

**B65H 29/12**; **B65H 31/04**; **B65B 25/14**

IPC 8 full level

**B65B 25/14** (2006.01); **B65H 29/12** (2006.01); **B65H 31/04** (2006.01); **B65H 31/24** (2006.01); **B65H 31/30** (2006.01)

CPC (source: EP)

**B65H 29/46** (2013.01); **B65H 29/51** (2013.01); **B65H 31/24** (2013.01); **B65H 31/3081** (2013.01); **B65H 2301/42266** (2013.01); **B65H 2701/1924** (2013.01)

Cited by

ITCR20090025A1; FR2685685A1; EP0891938A3; EP1097887A3; CN114161619A; FR2640896A1; ITCR20080026A1; EP0656309A1; AU682067B2; EP0171541A1; EP0347870A3; EP2147881A3; CN105228933A; JP2016526120A; EP0611720A1; US5356131A; US8517164B2; WO2010150070A1; WO0073188A1; EP2269927B1

Designated contracting state (EPC)

AT CH DE FR GB IT LI NL SE

DOCDB simple family (publication)

**EP 0076939 A1 19830420**; **EP 0076939 B1 19860226**; DE 3269420 D1 19860403; ES 516121 A0 19830601; ES 8306460 A1 19830601

DOCDB simple family (application)

**EP 82108652 A 19820918**; DE 3269420 T 19820918; ES 516121 A 19820930