

Title (en)
POSITIVE-DISPLACEMENT PRECISION PIPETTE

Publication
EP 0078724 B1 19850821 (FR)

Application
EP 82401913 A 19821019

Priority
FR 8120220 A 19811028

Abstract (en)
[origin: US4474071A] The pipette according to the invention has a body of the pipette at the lower end of which is fitted an end fitting of a calibrated capillary tube in which a piston is movable, and a gripping device at the upper end of the piston. It is characterized in that the piston has, in the region of its upper end intended to be gripped by the gripping device, a flange adapted to cooperate at its upper face with the free ends of the resilient fingers of the gripping device and by its lower face with an abutment surface arranged on the interior surface of the said end fitting of the capillary tube.

IPC 1-7
B01L 3/02

IPC 8 full level
B01L 3/02 (2006.01)

CPC (source: EP US)
B01L 3/0217 (2013.01 - EP US); **B01L 3/0279** (2013.01 - EP US)

Cited by
EP0421785A3; US5983733A; EP0226867A3; FR2882273A1; FR3012883A1; CN105705241A; EP3831486A1; EP0494735A3; EP3831487A1; WO2011128357A2; US9931626B2; US9931625B2; WO2006087444A1; WO2015067579A1; WO2011048168A1; WO2011048173A1; US8480972B2; WO2010086380A1; EP2924439A1; US9804064B2; WO2006030201A1; US8092394B2; WO9117833A3; WO2021110902A1

Designated contracting state (EPC)
AT BE CH DE FR GB IT LI LU NL SE

DOCDB simple family (publication)
EP 0078724 A1 19830511; EP 0078724 B1 19850821; AT E14994 T1 19850915; DE 3265643 D1 19850926; FR 2515339 A1 19830429; FR 2515339 B1 19840120; IE 53877 B1 19890329; IE 822582 L 19830428; JP H0153102 B2 19891113; JP S5884049 A 19830520; US 4474071 A 19841002

DOCDB simple family (application)
EP 82401913 A 19821019; AT 82401913 T 19821019; DE 3265643 T 19821019; FR 8120220 A 19811028; IE 258282 A 19821027; JP 18996382 A 19821028; US 42610382 A 19820928