

Title (en)
DOBBY OF THE ROTATION TYPE

Publication
EP 0078752 B2 19880706 (FR)

Application
EP 82420114 A 19820806

Priority
FR 8120502 A 19811029

Abstract (en)
[origin: ES8305436A1] The present invention relates to improvements in rotating dobbies. The control of the coupling pawl for connection to the driving shaft is effected by one of two right-angled pivoting levers actuated in the same zone by push elements of the reading device of the dobbie. When a lever engages in a notch in a plate fixed to the eccentric, the nose of the engaged one of the pivoting levers pushes a catch on the pawl which pivots the pawl causing the withdrawal of its finger to release connection with drive from the shaft.

IPC 1-7
D03C 1/00

IPC 8 full level
D03C 1/00 (2006.01); **D03C 1/14** (2006.01)

CPC (source: EP US)
D03C 1/00 (2013.01 - EP US)

Cited by
EP0212273A1; EP0116002A1; EP0163585A1; FR2563541A1; EP0444726A1

Designated contracting state (EPC)
CH DE IT LI

DOCDB simple family (publication)
EP 0078752 A1 19830511; EP 0078752 B1 19850220; EP 0078752 B2 19880706; DE 3262430 D1 19850328; ES 515230 A0 19830501; ES 8305436 A1 19830501; FR 2515702 A1 19830506; FR 2515702 B1 19831209; JP H0153371 B2 19891114; JP S5876544 A 19830509; US 4444225 A 19840424

DOCDB simple family (application)
EP 82420114 A 19820806; DE 3262430 T 19820806; ES 515230 A 19820825; FR 8120502 A 19811029; JP 17472282 A 19821006; US 40751282 A 19820812