

Title (en)
FLOORING

Publication
EP 0079066 B1 19860416 (DE)

Application
EP 82110257 A 19821108

Priority
DE 3144815 A 19811111

Abstract (en)
[origin: EP0079066A1] 1. Floor structure (10, 104, 106) for preferably damp work rooms such as kitchens or similar rooms with floor structure elements (12, 14, 32, 34, 36, 52, 54, 56, 84, 86, 108, 110, 112) which can be walked upon, placed at a certain distance to a supporting ceiling (16, 122, 124) and with elements arranged between the floor structure elements and the supporting ceiling which drain off liquid in a controlled manner and which in turn are placed at a certain distance to the supporting ceiling characterised in that the elements are protective elements (20, 58) protecting the supporting ceiling against liquid penetrating through the floor elements, the width of the said elements from edge to edge corresponding in each case to roughly the width of the corresponding floor structure element, and that the floor structure element with at least two opposite edges (88, 90, 142) interact with holding devices (22, 144) which are arranged on supporting elements (18, 138, 140) emanating directly or indirectly from the supporting ceiling (16, 124).

IPC 1-7
E04F 15/024

IPC 8 full level
E04F 15/024 (2006.01)

CPC (source: EP)
E04F 15/02405 (2013.01); **E04F 15/02435** (2013.01); **E04F 15/02452** (2013.01)

Cited by
DE3330739C1; EP0950776A1; EP4182519A4; US2012297713A1; US9192850B2; NL2028139B1; FR2266773A1; WO0118323A1; WO2023117985A1; US6574937B1; US6612084B2; WO2023117967A1; WO2022235157A1

Designated contracting state (EPC)
AT BE CH FR GB IT LI NL SE

DOCDB simple family (publication)
EP 0079066 A1 19830518; EP 0079066 B1 19860416; AT E19283 T1 19860515; DE 3144815 A1 19830526; DE 3144815 C2 19850620

DOCDB simple family (application)
EP 82110257 A 19821108; AT 82110257 T 19821108; DE 3144815 A 19811111