Title (en)

METHOD OF INSULATING OPENINGS IN BUILDING-WALLS

Publication

EP 0079254 B1 19850327 (FR)

Application

EP 82401849 A 19821008

Priority

FR 8120909 A 19811109

Abstract (en)

[origin: EP0079254A1] 1. Insulating system for the openings (2) in the facade of a building having exterior insulation (5) of the facade walls (1), and consisting, for each opening, of a shutter (9) made of a panel of insulating material, which is integrated into the exterior insulation, so as to allow the opening which is to be insulated to be sealed off when required, said shutter being mobile in a vertical plane parallel to the plane of the opening, characterised in that it consists, for each opening (2), of a housing in two parts (8, 8a) incorporated into the exterior insulation (5), one of said parts (8) being located to one side of the opening, while the other part (8a) is located to the opposite side of said opening, and also in that the dimensions of the shutter are slightly greater than those of the opening, so that in the open position said shutter is entirely contained within one of said parts (8) of the housing, and in the closed position said shutter is partially contained in both parts (8, 8a) of the housing.

IPC 1-7

E06B 9/04

IPC 8 full level

E06B 9/04 (2006.01)

CPC (source: EP)

E06B 9/04 (2013.01)

Cited by

WO2021152517A1; CH717102A1; FR2955141A1; FR2848239A1; FR2570407A2; FR2564877A1; DE212021000305U1

Designated contracting state (EPC)

AT DE GB IT NL SE

DOCDB simple family (publication)

EP 0079254 A1 19830518; **EP 0079254 B1 19850327**; AT E12422 T1 19850415; BE 894947 A 19830509; CH 650543 A5 19850731; DE 3262812 D1 19850502; FR 2516159 A1 19830513; FR 2516159 B1 19840316; LU 84422 A1 19830613

DOCDB simple family (application)

EP 82401849 Á 19821008; ÁT 82401849 T 19821008; BE 209426 A 19821108; CH 634582 A 19821101; DE 3262812 T 19821008; FR 8120909 A 19811109; LU 84422 A 19821012