

Title (en)
ROTARY DRUM

Publication
EP 0080040 A3 19830803 (DE)

Application
EP 82108734 A 19820921

Priority
DE 3145901 A 19811119

Abstract (en)
[origin: EP0080040A2] In the rotary drum envisaged according to the invention, an internally geared track ring (2) is supported via bearing plates (3) on the drum shell (1) and clamped free of play in the circumferential direction by wedges (4, 5). In a constructionally simple and yet extremely reliable manner, the bearing plates (3) are at the same time fastened to the track ring (2), while the wedges (4, 5) rest on abutments (6) which are fastened to the drum shell (1). <IMAGE>

IPC 1-7
F27B 7/22

IPC 8 full level
F27B 7/22 (2006.01)

CPC (source: EP)
F27B 7/2206 (2013.01)

Citation (search report)

- [YD] DE 939738 C 19560301 - POLYSIUS GMBH
- [Y] DE 1273268 B 19680718 - POLYSIUS GMBH
- [Y] DE 2011244 A1 19710923 - WEDAG WESTFALIA DINNENDAHL
- [A] DE 2512051 A1 19760930 - CREUSOT LOIRE
- [A] US 3096127 A 19630702 - SYM PARKER WILLIAM
- [A] GB 1124232 A 19680821 - FIVES LILLE CAIL
- [A] FR 2180319 A5 19731123 - KLOECKNER HUMBOLDT DEUTZ AG [DE]
- [A] FR 2415745 A2 19790824 - FIVES CAIL BABCOCK [FR]
- [A] EP 0012398 A1 19800625 - KRUPP POLYSIUS AG [DE]

Designated contracting state (EPC)
BE DE FR GB

DOCDB simple family (publication)
EP 0080040 A2 19830601; EP 0080040 A3 19830803; BR 8206612 A 19831004; DE 3145901 A1 19830630; ZA 827246 B 19830831

DOCDB simple family (application)
EP 82108734 A 19820921; BR 8206612 A 19821116; DE 3145901 A 19811119; ZA 827246 A 19821004