

Title (en)
HEEL BINDING

Publication
EP 0080060 B1 19851016 (DE)

Application
EP 82109545 A 19821015

Priority
AT 474381 A 19811105

Abstract (en)
[origin: US4533155A] A safety ski binding part includes a base plate having a roller supported thereon for rotation about a generally longitudinally extending axis, and a sole holder supported on the base plate for pivotal movement around a vertical axis and a transverse horizontal axis, the sole holder having a shoulder thereon. A lever supported on the base plate for pivotal movement about a transverse axis has a nose engageable with the shoulder and a transversely extending cam surface engageable with the roller. A release spring biases the lever in a direction urging the nose into engagement with the shoulder and urging the cam into engagement with the roller.

IPC 1-7
A63C 9/084

IPC 8 full level
A63C 9/085 (2006.01); **A63C 9/084** (2012.01); **A63C 9/00** (2012.01)

CPC (source: EP US)
A63C 9/0844 (2013.01 - EP US); **A63C 9/0845** (2013.01 - EP US); **A63C 9/0846** (2013.01 - EP US); **A63C 9/005** (2013.01 - EP US)

Cited by
FR2647689A1; EP0208206A3; EP2259850B1; EP2259850B2

Designated contracting state (EPC)
CH DE FR LI

DOCDB simple family (publication)
EP 0080060 A1 19830601; **EP 0080060 B1 19851016**; AT 372865 B 19831125; AT A474381 A 19830415; CA 1213297 A 19861028; DE 3266955 D1 19851121; JP S58130070 A 19830803; US 4533155 A 19850806

DOCDB simple family (application)
EP 82109545 A 19821015; AT 474381 A 19811105; CA 415023 A 19821105; DE 3266955 T 19821015; JP 19354482 A 19821105; US 43854982 A 19821101