

Title (en)

Support for drills for sharpening cutting edges.

Title (de)

Haltevorrichtung für Bohrer zum Schleifen der Schneiden.

Title (fr)

Support de forets pour l'affûtage des arêtes tranchantes.

Publication

EP 0080093 A2 19830601 (DE)

Application

EP 82110241 A 19821106

Priority

DE 3146664 A 19811125

Abstract (en)

[origin: US4547999A] This invention relates to a fixing device for fixing drills which are to be ground at their cutting edges. The fixing device comprises a baseplate, a stand carried by said baseplate, a pivot pin mounted on said stand near its top end, and a gripping device, which is slidably fitted on said pivot pin and adapted to grip the drill which is to be ground. The invention provides a simple and inexpensive fixing device of this type, which can be used for grinding twist drills or other drills, particularly by hobbyists, with adequate accuracy. In a device for fixing a drill which is to be ground at its cutting edges, comprising a baseplate, a stand carried by said baseplate, a pivot pin mounted on said stand near its top end, and a gripping device, which is fitted on said pivot pin and adapted to grip the drill which is to be ground, wherein said gripping device comprises a retaining member and prismatic members which extend transversely to said retaining member and are adapted to be adjusted relative to each other and to be fixed in position, a web of said retaining member carries a thrust screw for gripping a drill disposed between the prismatic members, and the prismatic members have end faces formed with blind bores for a fitting of the prismatic members on said pivot pin in different positions, that object is accomplished according in that the retaining member consists of a U-shaped guiding member, which embraces the prismatic members and extends into grooves formed on opposite sides of said prismatic members, one of said prismatic members constitutes an outer prismatic member, which is crew-connected to the end portions of the legs of the retaining member, the other of said prismatic members constitutes an inner prismatic member and is adapted to be displaced by said thrust screw so as to grip the drill between the prismatic members, and the prismatic members are formed in confronting surfaces with respective U-shaped longitudinal grooves, which are adapted to receive the drill.

Abstract (de)

Die Erfindung bezieht sich auf eine Haltevorrichtung für Bohrer zum Schleifen der Schneiden, bestehend aus einer Grundplatte, welche ein Standstück mit rechtwinkligem Achsbolzen am oberen Ende zum Aufstecken einer Einspanneinrichtung für den zu schleifenden Bohrer trägt, wobei eine einfachere und preiswertere Ausführung zum Anschleifen von Bohrern (Spiralbohrern), vor allem für Heimwerker, welche auch eine einwandfreie Genauigkeit ergeben, erreicht werden soll. Dies wird bei einer Haltevorrichtung nach dem Oberbegriff des Anspruchs 1 dadurch erreicht, daß ein Haltestück als U-förmiges Führungsstück die Prismen umgreifend in beidseitige U-Nuten derselben reicht, wobei das eine äußere Prisma in seiner Lage mit den Enden der Schenkel verschraubt und das innere Prisma mittels Druckschraube zum Einspannen des Bohrers verschiebbar ist und der Bohrer in zwei gegenüberliegenden, winkelförmigen Längsnuten zwischen den Prismen aufnehmbar ist.

IPC 1-7

B24B 3/26

IPC 8 full level

B24B 3/24 (2006.01); **B24B 3/26** (2006.01)

CPC (source: EP US)

B24B 3/247 (2013.01 - EP US); **B24B 3/26** (2013.01 - EP US)

Cited by

CN106217138A; KR101123896B1; CN106002503A; EP0143870A1; EP0256249A3

Designated contracting state (EPC)

AT BE CH FR GB IT LI NL SE

DOCDB simple family (publication)

EP 0080093 A2 19830601; **EP 0080093 A3 19840801**; **EP 0080093 B1 19870114**; AT E24856 T1 19870115; DE 3146664 C1 19830707; US 4547999 A 19851022

DOCDB simple family (application)

EP 82110241 A 19821106; AT 82110241 T 19821106; DE 3146664 A 19811125; US 44229782 A 19821117