

Title (en)

CONTACTOR WITH SELF-PROTECTION MEANS AGAINST THE REPULSIVE FORCES BETWEEN THE CONTACTS AND HIS APPLICATION IN
A CURRENT LIMITING CIRCUIT BREAKER

Publication

EP 0080939 B2 19900627 (FR)

Application

EP 82402146 A 19821125

Priority

FR 8122957 A 19811130

Abstract (en)

[origin: ES8308143A1] A contactor capable of having a very high breaking power comprises a movable contact carrier bridge (3) having a central part in the form of a blade (3c) and conducting J-shaped pieces (2a-2b) supporting fixed contacts. A non-magnetic blade bent in the form of a U is mounted slidable inside a hollow movable insulating contact holder (1) and guides and holds at its upper end a magnetic plate (8) cooperating with said blade (3c) and forming an air-gap with another U-shaped magnetic piece (6), disposed between the legs of the bent blade (5) and integral (at 7) with the contact holder (1). A contact pressure spring (4) bears on the basis of the U-shaped magnetic piece (6) and on the bottom of the bent blade (5).

IPC 1-7

H01H 1/54

IPC 8 full level

H01H 1/54 (2006.01); **H01H 77/10** (2006.01)

CPC (source: EP US)

H01H 77/101 (2013.01 - EP US)

Cited by

EP2197009A1; US9059523B2; US4634819A; EP2141714A3; FR2829869A1; FR2559308A1; FR2559307A1; CN112542331A; CN112563079A; EP2270829A1; FR2947667A1; CN101944442A; EP2372735A1; CN102208304A; EP2472538A1; EP2472539A1; WO2010066651A1; EP3014645B1; US9640355B2; US8946580B2

Designated contracting state (EPC)

AT CH DE GB IT LI SE

DOCDB simple family (publication)

EP 0080939 A1 19830608; EP 0080939 B1 19860402; EP 0080939 B2 19900627; AT E18959 T1 19860415; BR 8206904 A 19831004; CA 1182156 A 19850205; DE 3270302 D1 19860507; ES 517823 A0 19830816; ES 8308143 A1 19830816; FR 2517463 A1 19830603; FR 2517463 B1 19841102; IE 53984 B1 19890510; IE 822771 L 19830530; IN 159760 B 19870606; JP H0463489 B2 19921012; JP S58103719 A 19830620; MX 151968 A 19850522; US 4513270 A 19850423

DOCDB simple family (application)

EP 82402146 A 19821125; AT 82402146 T 19821125; BR 8206904 A 19821129; CA 416608 A 19821129; DE 3270302 T 19821125; ES 517823 A 19821130; FR 8122957 A 19811130; IE 277182 A 19821122; IN 871DE1982 A 19821124; JP 21052282 A 19821130; MX 19539582 A 19821130; US 44577482 A 19821130