

Title (en)
GULLY WITH FLUID ODOUR SEAL

Publication
EP 0081038 A3 19831005 (DE)

Application
EP 82108043 A 19820901

Priority
CH 780681 A 19811207

Abstract (en)
[origin: EP0081038A2] 1. Draining device for soil water from above, directly introduced household sewage water, waste water and similar, with a housing (1), which also has an inlet socket (25) on the side and a outlet socket (2), between which a liquid with a liquid level is being conducted, and in which liquid, in the housing (1) area, an insert separated from the housing, serving as odour seal (4) for liquids with a container (5) for liquids for filling from above is being installed, characterized in that the liquid container (5) is placed eccentric to the upper edge of the odour seal (4) and that the insert separated from the housing (1) has a drain edge (10) above a drain edge (28) of the outlet socket (2), which determines the liquid level (27) and consequently serves as second odour seal (26) for liquids together with the outer wall of the odour seal (4).

IPC 1-7
E03F 5/04

IPC 8 full level
E03F 5/04 (2006.01)

CPC (source: EP)
E03F 5/0405 (2013.01); **E03F 2005/0413** (2013.01); **E03F 2005/0416** (2013.01)

Citation (search report)

- [X] FR 700810 A 19310307
- [Y] CH 210559 A 19400731 - T MASCHINENBAU AKTIENGESELLSCH [CH]
- [Y] FR 2259948 A1 19750829 - SPANBERG B [SE]
- [A] CH 359103 A 19611215 - HANS U BOSSHARD FA [CH]
- [A] CH 155378 A 19320630 - CRETIN GEB [CH]
- [A] CH 525343 A 19720715 - VON ROLL AG [CH]

Cited by
FR2569244A1; CN101886425A; EP0124888A3; EP1571269A1; GB2155967A; DE3918321A1; DE3918321C2; AT393397B; WO9844210A1

Designated contracting state (EPC)
AT DE FR GB IT NL SE

DOCDB simple family (publication)
EP 0081038 A2 19830615; EP 0081038 A3 19831005; EP 0081038 B1 19860813; AT E21424 T1 19860815; CH 655150 A5 19860327; DE 3272582 D1 19860918

DOCDB simple family (application)
EP 82108043 A 19820901; AT 82108043 T 19820901; CH 780681 A 19811207; DE 3272582 T 19820901