

Title (en)

METHOD OF APPLYING A FIXATING LIQUID TO TEXTILE WEB MATERIALS PRINTED OR DYED WITH REACTIVE DYES

Publication

**EP 0081134 B1 19870318 (DE)**

Application

**EP 82110799 A 19821123**

Priority

DE 3147318 A 19811128

Abstract (en)

[origin: EP0081134A1] 1. Process for the continuous application of alkaline fixing liquors on unfixed, previously with reactive dyestuffs without addition of alkali treated and eventually dried textile webs made of cellulosic fibres or their mixtures with polyester fibers, by means of atomizing with rotating spraying nozzles on the passing textile webs in a uniform layer covering the printed or pad dyed areas, fixing liquors of higher viscosity, based on solutions of sodium silicate with a density of 37 to 50 degrees Be identical with a specific gravity of 1,34 to 1,53 by means of rotating nozzles with 3000 to 7000 revolutions per minute and a spraying width of 5 to 20 cm per rotating nozzle.

IPC 1-7

**D06B 19/00; D06B 5/10**

IPC 8 full level

**B05D 7/00** (2006.01); **B05D 1/02** (2006.01); **D06B 5/10** (2006.01); **D06B 19/00** (2006.01); **D06P 5/02** (2006.01); **D06P 7/00** (2006.01)

CPC (source: EP)

**D06B 5/10** (2013.01); **D06B 19/0064** (2013.01)

Designated contracting state (EPC)

CH DE FR GB IT LI

DOCDB simple family (publication)

**EP 0081134 A1 19830615; EP 0081134 B1 19870318**; DE 3147318 A1 19830601; DE 3275740 D1 19870423; JP S5898485 A 19830611

DOCDB simple family (application)

**EP 82110799 A 19821123**; DE 3147318 A 19811128; DE 3275740 T 19821123; JP 20628082 A 19821126