

Title (en)

METHOD OF AND DEVICE FOR WINDING THE INDUCTIVE COILS EQUIPPING ELECTRICAL APPARATUSES SUCH AS TRANSFORMERS

Publication

EP 0081446 B1 19860611 (FR)

Application

EP 82440037 A 19821119

Priority

FR 8122614 A 19811201

Abstract (en)

[origin: ES8308444A1] An insulated wire is wound into a cylindrical coil by being continuously introduced into an annular space between a cylindrical core and a cylindrical sleeve coaxially surrounding same above a supporting surface which is rotated about their axis at an angular velocity W, the wire being fed in at a linear speed V. A processor is programmed to vary the ratio V/W according to the relationship $(V/W)i = \pi [D+2d](ai-1)$ where D is the diameter of the core, d is the wire diameter and ai is an integer representing the order number of the ith turn of a spiral path, counted from the core surface, along which the wire is laid in a succession of flat layers piled one atop the other. Each layer consists of n contiguous turns following one another in a radially outward direction in odd-numbered layers and in a radially inward direction in even-numbered layers, with decrementation or incrementation of the ratio V/W at the end of each turn. The discharge end of a feed tube is raised above the supporting surface, upon the completion of each layer, by an incremental distance equal to the wire diameter d to accommodate the next layer.

IPC 1-7

B65H 54/80; H01F 41/06

IPC 8 full level

H01F 41/04 (2006.01); **B65H 54/80** (2006.01); **H01F 41/06** (2006.01)

CPC (source: EP KR US)

B65H 54/80 (2013.01 - EP KR US); **H01F 41/06** (2013.01 - KR); **H01F 41/096** (2016.01 - EP US)

Cited by

EP0448977A3; EP0674328A1; US5547532A; EP0923783B1

Designated contracting state (EPC)

AT BE CH DE FR GB IT LI LU NL SE

DOCDB simple family (publication)

EP 0081446 A1 19830615; EP 0081446 B1 19860611; AT E20331 T1 19860615; CA 1206733 A 19860702; DE 3271688 D1 19860717; DK 159223 B 19900917; DK 159223 C 19910225; DK 531382 A 19830602; ES 517797 A0 19830816; ES 8308444 A1 19830816; FR 2517462 A1 19830603; FR 2517462 B1 19861003; IE 53970 B1 19890426; IE 822844 L 19830601; JP H0430170 B2 19920521; JP S58161310 A 19830924; KR 840003133 A 19840813; KR 880001084 B1 19880622; PT 75919 A 19821201; PT 75919 B 19850125; SG 26289 G 19890922; US 4491284 A 19850101

DOCDB simple family (application)

EP 82440037 A 19821119; AT 82440037 T 19821119; CA 415916 A 19821118; DE 3271688 T 19821119; DK 531382 A 19821130; ES 517797 A 19821130; FR 8122614 A 19811201; IE 284482 A 19821130; JP 21117882 A 19821201; KR 820005388 A 19821201; PT 7591982 A 19821130; SG 26289 A 19890419; US 44603082 A 19821201