

Title (en)

METHOD OF PRODUCING A HOLLOW FOUNDRY CORE

Publication

**EP 0083713 B1 19850220 (DE)**

Application

**EP 82110751 A 19821120**

Priority

DE 3200193 A 19820107

Abstract (en)

[origin: US4694883A] An apparatus for producing a hollow foundry core, whereby core halves are first formed and fully hardened on an inner hollow-mold part and an outer mold-box half. These core halves are then sprayed with an adhesive and joined to form a finished foundry core. The apparatus reduces the production costs and improves the accuracy as to the size of the cores. The forming of the core halves on a center plate and the bringing together of the core halves respectively occurs by moving together both core-box halves in one operation.

IPC 1-7

**B22C 9/00**; **B22C 9/10**; **B22C 9/24**; **B22C 13/12**

IPC 8 full level

**B22C 9/00** (2006.01); **B22C 9/10** (2006.01); **B22C 9/12** (2006.01); **B22C 9/24** (2006.01); **B22C 13/08** (2006.01); **B22C 13/12** (2006.01)

CPC (source: EP US)

**B22C 9/103** (2013.01 - EP US)

Cited by

EP0904872A1; EP0209809A3; EP1134048A1; EP0280675A3; EP2022579A1; US6588490B2; WO0124957A1; WO0071282A1; WO0023214A1; WO8707543A1

Designated contracting state (EPC)

DE FR GB IT SE

DOCDB simple family (publication)

**EP 0083713 A2 19830720**; **EP 0083713 A3 19831005**; **EP 0083713 B1 19850220**; DE 3200193 A1 19830714; DE 3262453 D1 19850328; JP S58119435 A 19830715; US 4694883 A 19870922

DOCDB simple family (application)

**EP 82110751 A 19821120**; DE 3200193 A 19820107; DE 3262453 T 19821120; JP 22646582 A 19821224; US 81055185 A 19851218