

Title (en)

Method for closing off an open end of a multilayered tube and a multilayered parison structure.

Title (de)

Verfahren zum Verschliessen eines offenen Endes eines mehrschichtigen Rohrs und mehrschichtiger Vorformling.

Title (fr)

Procédé pour fermer un bout ouvert d'un tube à parois multiples et ébauche à parois multiples.

Publication

EP 0083722 A1 19830720 (EN)

Application

EP 82110878 A 19821124

Priority

US 32962581 A 19811211

Abstract (en)

[origin: US4424182A] A method is disclosed for sealing or closing off the open end of a multilayered tubular structure, especially one having a barrier or low-gas permeable layer, whereby the integrity of said barrier layer is maintained. The method gives rise to a multilayered parison structure which comprises a cylindrical body having a body wall, an open portion terminating at one end thereof and a bottom wall at the opposite end of said body, said body and bottom walls being composed of a plurality of layers bonded together, all the layers of said bottom wall extending fully inwardly in contacting and overlapping relationship with like layers along the longitudinal axis of said cylindrical body, and a balancing member attached to said bottom wall, said member being composed of a single layer material forced therefrom while in a plastic state.

IPC 1-7

B29C 17/07

IPC 8 full level

B29B 13/02 (2006.01); **B29C 49/22** (2006.01); **B29C 57/10** (2006.01); **B29C 65/02** (2006.01); **B29C 65/14** (2006.01)

CPC (source: EP US)

B29B 13/025 (2013.01 - EP US); **B29C 49/22** (2013.01 - EP US); **B29C 57/10** (2013.01 - EP US); **B29C 65/02** (2013.01 - EP US); **B29C 65/14** (2013.01 - EP US); **B29C 65/1454** (2013.01 - EP US); **B29C 66/1122** (2013.01 - EP US); **B29C 66/43121** (2013.01 - EP US); **B29C 66/52272** (2013.01 - EP US); **B29C 66/545** (2013.01 - EP US); **B29C 66/72341** (2013.01 - EP US); **B29C 66/73921** (2013.01 - EP US); **B29C 66/83413** (2013.01 - EP US); **B29C 2793/0027** (2013.01 - EP US); **B29C 2949/3008** (2022.05 - EP US); **B29C 2949/3012** (2022.05 - EP US); **B29C 2949/3016** (2022.05 - EP US); **B29C 2949/302** (2022.05 - EP US); **B29C 2949/3028** (2022.05 - EP US); **B29C 2949/3044** (2022.05 - EP US); **B29L 2009/00** (2013.01 - EP US)

Citation (search report)

- [A] DE 2821257 A1 19790405 - TOPPAN PRINTING CO LTD
- [A] DE 2543640 A1 19770407 - GILDEMEISTER CORPOPLAST GMBH
- [A] US 4149839 A 19790417 - IWAWAKI AKIRA, et al
- [A] DE 2249865 B2 19771020
- [A] US 4079664 A 19780321 - JONES MILTON E
- [AD] US 3430290 A 19690304 - KINSLOW WILLIAM G JR
- [AD] US 3955697 A 19760511 - VALYI EMERY I
- [AD] US 3686379 A 19720822 - GILBERT DIXIE E
- [A] PLAST VERARBEITER, Vol. 30, No. 4, April 1979, Speyer am Rhein, W. DAUBENBÜCHEL et al. "Gezielte Verbesserung der Eigenschaften von Hohlkörpern durch Coextrusion", pages 197-201

Cited by

EP0167160A3; FR2560114A1; FR2582253A1; FR2629752A1; BE1003121A3

Designated contracting state (EPC)

AT BE CH DE FR GB IT LI LU NL SE

DOCDB simple family (publication)

EP 0083722 A1 19830720; US 4424182 A 19840103

DOCDB simple family (application)

EP 82110878 A 19821124; US 32962581 A 19811211