

Title (en)

METHOD AND DEVICE OF REMOVING A BROKEN WEFT YARN IN A JET LOOM

Publication

EP 0083748 B1 19860430 (DE)

Application

EP 82111493 A 19821210

Priority

JP 20060081 A 19811211

Abstract (en)

[origin: US4520849A] In a fluid jet loom in general, the loom operation is not stopped immediately after detection of the defective weft yarn, resulting unavoidably in the insertion of the next weft yarn. In this regard, the present invention provides a method for disposal of the defective weft yarn in a fluid jet loom which consists in temporarily disabling the weft yarn cutting function of a weft yarn cutter provided to the weft yarn inserting nozzle upon detection of defective weft yarn insertion, and subsequently stopping the loom operation.

IPC 1-7

D03D 47/30

IPC 8 full level

D03D 49/70 (2006.01); **D03D 47/30** (2006.01); **D03D 51/00** (2006.01); **D03D 51/08** (2006.01)

CPC (source: EP KR US)

D03D 47/30 (2013.01 - KR); **D03D 51/085** (2013.01 - EP US)

Cited by

US4749006A; EP0200168A3; US4576208A

Designated contracting state (EPC)

BE CH DE LI

DOCDB simple family (publication)

EP 0083748 A1 19830720; **EP 0083748 B1 19860430**; BR 8207183 A 19831011; DE 3270904 D1 19860605; JP H0262619 B2 19901226; JP S58104247 A 19830621; KR 840002475 A 19840702; KR 850001578 B1 19851019; US 4520849 A 19850604

DOCDB simple family (application)

EP 82111493 A 19821210; BR 8207183 A 19821210; DE 3270904 T 19821210; JP 20060081 A 19811211; KR 820005290 A 19821124; US 44751182 A 19821207