

Title (en)  
BUCKLE FOR A SAFETY BELT

Publication  
**EP 0083752 B1 19880323 (DE)**

Application  
**EP 82111564 A 19821214**

Priority  
DE 3200770 A 19820113

Abstract (en)  
[origin: ES269633U] In a buckle for a safety belt a pivotable locking bar (13-17) is arranged in relation to the push-in tongue (4) in such a way that the ejector force (11) or the belt force exerting a load on the tongue urges the locking bar out of engagement. To prevent this in the closing position, there is a pivoting lever (21) which can be pivoted as a result of actuation of a slide (27) so that the locking bar (13-17) and consequently the push-in tongue (4) are released. According to the invention, this releasing pivoting movement of the locking bar is assisted because an extension piece (30) is provided on the slide (27) and a projection (32) interacting therewith is provided on the locking bar (13-17), and by means of these, when the slide (27) is pressed in, an additional torque for pivoting the locking bar into the opened position is transmitted.

IPC 1-7  
**A44B 11/25**

IPC 8 full level  
**A44B 11/25** (2006.01)

CPC (source: EP US)  
**A44B 11/2523** (2013.01 - EP US); **Y10T 24/45644** (2015.01 - EP US); **Y10T 24/45665** (2015.01 - EP US)

Cited by  
EP0719506A3; EP0364970A3; US5067211A; EP0252403A1; EP0566856A1; DE4123280C2; FR2659919A1; US5555609A; FR2621229A1; DE4422224A1; DE4422224C2; FR2608982A1; FR2657572A1; FR2644329A1; GB2249806A; GB2249806B; US6438810B2; WO9408480A1; WO0149144A1; WO9010397A1

Designated contracting state (EPC)  
DE FR GB IT SE

DOCDB simple family (publication)  
**EP 0083752 A2 19830720; EP 0083752 A3 19851204; EP 0083752 B1 19880323**; DE 3200770 A1 19830721; DE 3278262 D1 19880428; ES 269633 U 19830701; ES 269633 Y 19840116; JP H0376923 B2 19911209; JP S58124401 A 19830725; US 4527317 A 19850709

DOCDB simple family (application)  
**EP 82111564 A 19821214**; DE 3200770 A 19820113; DE 3278262 T 19821214; ES 269633 U 19830110; JP 514583 A 19830113; US 45658783 A 19830107