

Title (en)

TERRY LOOM HAVING AN EXPANDER DEVICE BETWEEN THE REED AND THE BREAST BEAM

Publication

EP 0083905 B1 19850807 (DE)

Application

EP 82810010 A 19820113

Priority

EP 82810010 A 19820113

Abstract (en)

[origin: US4485848A] The terry weaving machine is provided with a deflecting mechanism for guiding the edge warp yarns therethrough to retain the tucked-in end of a weft yarn in tong-like fashion. The deflecting mechanism may be in the form of a plate with a single slot or may be defined by a pair of adjustable jaws so that the slot can be sized depending upon the size and type of yarns being woven.

IPC 1-7

D03D 47/48; D03D 39/22

IPC 8 full level

D03D 39/22 (2006.01); **D03D 47/48** (2006.01)

CPC (source: EP US)

D03D 39/223 (2013.01 - EP US); **D03D 47/48** (2013.01 - EP US)

Cited by

AT378790B; EP1055753A1; EP0695821A1; DE19712280A1; EP0443343A1; FR2547326A1; US6240975B1

Designated contracting state (EPC)

CH DE FR IT LI

DOCDB simple family (publication)

EP 0083905 A1 19830720; EP 0083905 B1 19850807; EP 0083905 B2 19901031; DE 3265120 D1 19850912; US 4485848 A 19841204

DOCDB simple family (application)

EP 82810010 A 19820113; DE 3265120 T 19820113; US 45043782 A 19821216