

Title (en)
HEAT-INSULATING COMPOUND PROFILE

Publication
EP 0085775 B1 19850807 (DE)

Application
EP 82111610 A 19821214

Priority
DE 3200844 A 19820114

Abstract (en)
[origin: EP0085775A1] 1. A heat-insulating composite member, in particular for window or door frames, comprising two metal bar sections (1, 2, 1a, 2a) and an insulating strip (3) connecting same, wherein the metal bar sections have strip portions (6, 7; 17, 18) which extend continuously at both longitudinal sides of the insulating strip and which engage into recesses in the insulating strip, and provided on each bar section between the continuous strip portions is an intermediate web portion (12, 13) which engages into a groove (10, 11) in the insulating strip, wherein the intermediate web portions extend at an inclined angle with respect to the continuous strip portions at one longitudinal side of the insulating strip and the internal width of the grooves is greater than the thickness of the intermediate web portions and the continuous strip portions (6, 7) towards which the intermediate web portions are directed are deformed and pivoted by an applied pressure from the exterior about an axis (A) extending parallel to the longitudinal direction of the associated metal bar section, in such a way that the strip portions (6, 7) press the insulating strip against the metal bar sections in the region between the intermediate web portions and the continuous strip portions, and the insulating strip is provided with edge strip portions (25), at the side that the intermediate web portions are directed away from, characterised in that each edge strip portion (25) engages into a receiving groove (28) in the metal bar section, which receiving groove is provided with a pivotable and cold-deformable inner web portion (22, 30), the inner web portion forms the inside wall of the receiving groove and is pivotable about an axis (B) extending parallel to the longitudinal direction of the associated metal bar section (1, 2; 1a, 2a), there is a gap between the bottom (29) of the receiving groove (28) and the edge strip portion (25), and the edge strip portion (25) is gripped between the inner web portion (22, 30) and the inside wall (26) of the metal bar section.

IPC 1-7
E06B 3/26

IPC 8 full level
E06B 3/26 (2006.01); **E06B 3/273** (2006.01); **E06B 3/263** (2006.01)

CPC (source: EP)
E06B 3/273 (2013.01); **E06B 2003/26352** (2013.01)

Cited by
EP0172575A3; CN109458112A; EP0200171A1; EP1215360A1; ES2112690A1; GB2371076A; GB2371076B; WO0220930A1

Designated contracting state (EPC)
BE GB IT LU NL

DOCDB simple family (publication)
EP 0085775 A1 19830817; EP 0085775 B1 19850807; CA 1222165 A 19870526; DE 3200844 A1 19830721; DK 11183 A 19830715; DK 11183 D0 19830113; DK 152815 B 19880516; DK 152815 C 19881010; FI 77318 B 19881031; FI 77318 C 19890210; FI 830103 A0 19830112; FI 830103 L 19830715; JP H0346636 B2 19910716; JP S58127887 A 19830730; NO 161135 B 19890328; NO 161135 C 19890705; NO 830094 L 19830715

DOCDB simple family (application)
EP 82111610 A 19821214; CA 419421 A 19830113; DE 3200844 A 19820114; DK 11183 A 19830113; FI 830103 A 19830112; JP 180983 A 19830111; NO 830094 A 19830113