

Title (en)

INTERLOCKING DEVICE FOR THE JOINING TOGETHER OF TWO ELEMENTS PLACED OPPOSITE ONE ANOTHER

Publication

EP 0085998 B1 19851121 (EN)

Application

EP 83200060 A 19830117

Priority

BE 1010400 A 19820118

Abstract (en)

[origin: GB2114210A] A hook bolt 10 is guided by pins 16 engaging slots 17, 18 in a housing 1, to rotate into a projecting position as pins 16 follow slots 17, and then to withdraw towards the housing 1 to positively engage a pin 12 as pins 16 follow slots 18. The bolt 10 is moved by a key or the like engaged in a member 7 having a lug 9 which bears on a surface 23 of an aperture 20 in the bolt. <IMAGE>

IPC 1-7

E05C 19/12; E05B 65/08; E05C 3/06; E05C 5/00

IPC 8 full level

E04B 1/61 (2006.01); **E05B 65/08** (2006.01)

CPC (source: EP)

E04B 1/6183 (2013.01); **E05B 65/0817** (2013.01)

Cited by

EP1471190A3; GB2287744A; GB2436119A; GB2436119B; DE4121247A1; DE4121247C2

Designated contracting state (EPC)

DE FR LU NL

DOCDB simple family (publication)

GB 2114210 A 19830817; **GB 2114210 B 19860312**; **GB 8301316 D0 19830216**; DE 3361242 D1 19860102; EP 0085998 A1 19830817; EP 0085998 B1 19851121

DOCDB simple family (application)

GB 8301316 A 19830118; DE 3361242 T 19830117; EP 83200060 A 19830117