

Title (en)

PROCEDURE AND TOOL FOR MOUNTING ELONGATED CYLINDRICAL ELEMENTS IN PREDRILLED HOLES

Publication

EP 0086418 A3 19840912 (EN)

Application

EP 83101100 A 19830207

Priority

SE 8200827 A 19820211

Abstract (en)

[origin: EP0086418A2] In a procedure for mounting elongated cylindrical elements in predrilled holes the element (5) is first fitted with resilient retention in one end of an axial through hole (2) in a sleeve (1). Accommodated at the other end of the hole (2) is a striker (3). The sleeve (1) with the cylindrical element (5) is applied to the mouth of the predrilled hole and the striker (3) is then subjected to blows so that it strikes the element (5) and drives it into the hole. A tool for implementing the procedure embraces a sleeve (1) with an axial through hole (2). One end of the hole (2) is arranged to accommodate an elongated striker (3) and the other end to accommodate the cylindrical element (5) which is retained in the sleeve (1) by spring pressure.

IPC 1-7

B25C 3/00

IPC 8 full level

B25B 27/04 (2006.01); **B25C 3/00** (2006.01)

CPC (source: EP)

B25B 27/04 (2013.01); **B25C 3/006** (2013.01)

Citation (search report)

- [X] US 3788537 A 19740129 - FOX W
- [Y] FR 2291001 A2 19760611 - CHATARD HENRI [FR]
- [X] US 2973520 A 19610307 - WALTER BELL LEWIS
- [X] US 3036482 A 19620529 - KENNETH KENWORTHY, et al
- [Y] US 3979978 A 19760914 - SMOLIK ROBERT A
- [X] US 2839754 A 19580624 - PFAFF ELMER F

Cited by

EP1506844A1; CN106985121A; CN103978460A; CN110270964A; US7021164B2

Designated contracting state (EPC)

CH DE FR GB IT LI

DOCDB simple family (publication)

EP 0086418 A2 19830824; EP 0086418 A3 19840912; SE 8200827 L 19830812

DOCDB simple family (application)

EP 83101100 A 19830207; SE 8200827 A 19820211